

Specification Sheet

Part Number: 170-03205



Tightly woven fabric bundles and protects cables and hoses from sunlight and abrasion damage; also deflects high pressure hose ruptures. Nylon material resists gasoline, salt and other chemicals.

Cut to size easily with regular scissors.

Braided Sleeving, Heavy Duty, 2" Dia, PA6, Black, 50 ft/reel

| | |
|---------------------|--|
| Article Number | 170-03205 |
| Type | BSHDWV |
| Color | Black (BK) |
| Quantity Per | box |
| Product Description | Sleeving made of a tightly woven nylon fabric, slides onto hoses, cables and components to protect them from abrasion and environmental elements, including UV damage. Also protects surrounding surfaces from damage. |
| Short Description | Braided Sleeving, Heavy Duty, 2" Dia, PA6, Black, 50 ft/reel |
| Global Part Name | BSHDWV-PA6-BK |

| | |
|--------------------------------|-------------------|
| Length L (Imperial) | 50.0 |
| Length L (Metric) | 15.24 |
| Bundle Diameter Min (Imperial) | 0.1 |
| Bundle Diameter Min (Metric) | 2.54 |
| Bundle Diameter Max (Imperial) | 2.0 |
| Bundle Diameter Max (Metric) | 50.8 |
| Diameter D (Imperial) | 2.07 |
| Diameter D (Metric) | 50.58 |
| Nominal Diameter (Imperial) | 2 |
| Nominal Diameter (Metric) | 50.8 |
| Wall Thickness WT (Imperial) | .045 |
| Wall Thickness WT (Metric) | 1.14 |
| Material | Polyamide 6 (PA6) |
| Material Shortcut | PA6 |
| Flammability | Non-flammable |

| | |
|------------------------------|-----------------------------------|
| Halogen Free | Yes |
| Operating Temperature | -49°F to +248°F (-45°C to +120°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 50 |
| Package Quantity (Metric) | 15.24 |
| Customs Number | 5806322000 |

© 2022 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)