

## Specification Sheet

Part Number: 170-03208



Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.

Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.

Braided Sleeving, Expandable, Flame Retardant, 0.75" Dia, PET, Black, 1300 ft/reel

**Article Number** 170-03208

**Type** BSPFR340

**Color** Black (BK)

**Quantity Per** box

**Product Description** A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.

**Short Description** Braided Sleeving, Expandable, Flame Retardant, 0.75" Dia, PET, Black, 1300 ft/reel

**Global Part Name** BSPFR340-PET-BK

**Length L (Imperial)** 1300.0

**Length L (Metric)** 396.24

**Bundle Diameter Min (Imperial)** 0.5

**Bundle Diameter Min (Metric)** 12.7

**Bundle Diameter Max (Imperial)** 1.25

**Bundle Diameter Max (Metric)** 31.75

**Diameter D (Imperial)** 0.75

**Diameter D (Metric)** 19.05

**Nominal Diameter (Imperial)** 0.75

**Nominal Diameter (Metric)** 19.05

**Material** Polyester (PET)

**Material Shortcut** PET

**Flammability** UL VW-1 FAR 25 FMVSS 302 Mil-202

**Halogen Free** Yes

**Operating Temperature** -94°F to +248°F (-70°C to +120°C)

**Reach Compliant (Article 33)** Yes

**ROHS Compliant** Yes

**UL Recognized (US)** Yes

**UL Recognized (US and Canada)** Yes

**Package Quantity (Imperial)** 1300

**Package Quantity (Metric)** 396.24

**Customs Number** 5808100000