

Specification Sheet

Part Number: 170-03210



Resists fuels, salts and solvents, gasoline, and other common contaminants. Nylon monofilament construction weave offers a tight, 12 mil braid that provides full coverage but will not rot or retain moisture. Material performs well in wet applications and where abiding substrate has a smooth surface. Expands up to 150% of flat diameter for easy installation.

Braided Sleeving, Expandable, 0.62" Dia, PA66 Monofilament, Black, 100 ft/reel

Article Number 170-03210

Type BSPA66580

Color Black (BK)

Quantity Per box

Product Description A pliable yet durable nylon sleeve that protects against cuts, abrasion and excessive wear caused by repetitive motion. Used on hoses, pipes, wiring harnesses and cables installed in cars, trucks, military vehicles, trains and industrial equipment. Protects delicate wiring in engine compartments and near exhaust systems or used to organize wires and breakouts in electrical harnesses.

Short Description Braided Sleeving, Expandable, 0.62" Dia, PA66 Monofilament, Black, 100 ft/reel

Global Part Name BSPA66580-PA66-BK

Length L (Imperial) 100.0

Length L (Metric) 30.48

Bundle Diameter Min (Imperial) 0.1

Bundle Diameter Min (Metric) 2.54

Bundle Diameter Max (Imperial) 0.6

Bundle Diameter Max (Metric) 15.2

Diameter D (Imperial) 0.625

Diameter D (Metric) 15.88

Nominal Diameter (Imperial) 0.62

Nominal Diameter (Metric) 15.88

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability Non-Flammable

Halogen Free	Yes
Operating Temperature	-49°F to +302°F (-45°C to +150°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	30.48
Customs Number	5808100000

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)