

## Specification Sheet

Part Number: 170-03213

Center-slit overlapping design allows quick and easy access to the wires and cables for future maintenance or inspection without disassembly. Flexible material allows it to easily wrap around a variety of component shapes and sizes, making it easier to use than slit-loom tubing or spiral-wrap materials.

A unique weave pattern provides increased coverage and greater resistance to abrasion, dust and debris.

Overlapping design enhances flexibility, allowing it to shift and bend without exposing wire and cables.



Braided Sleeving, Split Wrap, 0.38" Dia, PET, Black, 1500 ft/Large bulk reel

Article Number 170-03213

Type BSPSW380LB

Color Black (BK)

Quantity Per reel

Product Description A lateral split semi-rigid braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.

|                                |  |
|--------------------------------|--|
| Short Description              | Braided Sleeving, Split Wrap, 0.38" Dia, PET, Black, 1500 ft/Large bulk reel |
| Global Part Name               | BSPSW380LB-PET-BK  |
| Length L (Imperial)            | 1500.0   |
| Bundle Diameter Min (Imperial) | 0.1  |
| Bundle Diameter Min (Metric)   | 2.54   |
| Bundle Diameter Max (Imperial) | 0.38   |
| Bundle Diameter Max (Metric)   | 9.6  |
| Diameter D (Imperial)          | 0.38   |
| Diameter D (Metric)            | 9.6  |
| Nominal Diameter (Imperial)    | 0.38   |
| Nominal Diameter (Metric)      | 9.5  |
| Material                       | Polyester (PET)  |
| Material Shortcut              | PET  |
| Flammability                   | UL 94 V-0  |

|                              |                                   |
|------------------------------|-----------------------------------|
| Halogen Free                 | Yes                               |
| Operating Temperature        | -94°F to +257°F (-70°C to +125°C) |
| Reach Compliant (Article 33) | Yes                               |
| ROHS Compliant               | Yes                               |
| UL Recognized (US)           | Yes                               |
| Package Quantity (Imperial)  | 1500                              |
| Package Quantity (Metric)    | 457.20                            |
| Customs Number               | 5808100000                        |

© 2022 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)