

Specification Sheet

Part Number: 170-03221

Split wrap design needs no fasteners and installs quickly, saving assembly time and future accessibility without disassembly.

Bends to a tight radius without distortion or splitting open.

Unique construction retains shape and rigidity throughout unrolling.

Added flame-inhibitor fibers extinguish quickly and reduces potential flame spread to surrounding components.

Easy open design allows quick access and ability to apply protective sleeving post assembly or post installation situations.



Braided Sleeving, Split Wrap Woven, Flame Retardant, 1-1/4" Dia, PET, Black, 75 ft/bulk reel

Article Number	170-03221
Type	BSSWVFR1140B
Color	Black (BK)
Quantity Per	reel

Product Description	A lateral split, semi-rigid and flame retardant braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires. More flexible than spiral wraps or convoluted tubing, this product is a fast and easy option for adding protection in post-assembly or post-installation applications. Meets NFPA 130 rail market applications.
Short Description	Braided Sleeving, Split Wrap Woven, Flame Retardant, 1-1/4" Dia, PET, Black, 75 ft/bulk reel
Global Part Name	BSSWVFR1140B-PET-BK
Length L (Imperial)	75.0
Length L (Metric)	22.9
Bundle Diameter Min (Imperial)	0.1
Bundle Diameter Min (Metric)	2.54
Bundle Diameter Max (Imperial)	1.25
Bundle Diameter Max (Metric)	31.8
Diameter D (Imperial)	1.25
Diameter D (Metric)	31.8
Nominal Diameter (Imperial)	1.25
Nominal Diameter (Metric)	31.8

Wall Thickness WT (Imperial)	0.027
Wall Thickness WT (Metric)	0.68
Material	Polyester (PET)
Material Shortcut	PET
Flammability	UL VW-1
Halogen Free	Yes
UV Resistant (Yes/No)	No
Operating Temperature	-94°F to +257°F (-70°C to +125°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	Exova NFPA130: 2017 ASTM E 662 ASTM E 162 ASTM 1354
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity (Imperial)	75
Package Quantity (Metric)	22.86

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).