

Specification Sheet

Part Number: 170-21000



Nylon monofilament construction weave offers a tight braid that provides full coverage but will not rot or retain moisture.

Material performs well in wet applications and where abiding substrate has a smooth surface.

Helagaine Braided Sleeving, 10 mm Dia, PA66, GY, 328ft/Reel

Article Number 170-21000

Type HEGPA6610

Color Gray (GY)

Quantity Per metre

Product Description Helagaine Nylon Polyamide Expandable Braided Sleeving is a pliable yet durable sleeve that protects against cuts, abrasion and excessive wear caused by repetitive motion.

Short Description Helagaine Braided Sleeving, 10 mm Dia, PA66, GY, 328ft/Reel

Global Part Name HEGPA6610-PA66-GY

Length L (Imperial)	328.0
Length L (Metric)	100.0
Bundle Diameter Min (Imperial)	0.28
Bundle Diameter Min (Metric)	7
Bundle Diameter Max (Imperial)	0.47
Bundle Diameter Max (Metric)	12
Diameter D (Imperial)	0.39
Diameter D (Metric)	9.9
Nominal Diameter (Imperial)	0.38
Nominal Diameter (Metric)	10
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V2 FMVSS 302
Halogen Free	Yes
Operating Temperature	-76°F to +302°F (-60°C to +150°C)

Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	RST-LAB ECE R-118-03 Abschnitt 8 / Annex 8 (PB60-18-0688, PB60-18-0689) RST LAB DIN EN [45545-2] (02/2016) EDAG-LAB ECE R-118-03 Abschnitt 6 / Annex 6 (PB-58022-0019-02)
Package Quantity (Imperial)	328
Package Quantity (Metric)	100
Customs Number	5808100000