

## Specification Sheet

Part Number: PR1M4



Panel Rivet, PA66, Natural, 1000/bag

**Article Number**

181-00139

**Type**

PR1

**Color**

Natural (NA)

### Features & Benefits

- Panel rivets are made with nylon material to hold duct securely to the panel without corroding, ensuring longevity.
- Panel rivets can be easily inserted with use of a specially designed, long shafted panel rivet tool.
- Ergonomic design of the tool ensures effortless use when inserting rivets into deep channels or locations difficult to access.

**Quantity Per**

EA

### Product Description

HellermannTyton panel rivets are one piece drive rivets that provide a fast, economic means of affixing wiring duct. The rivet is inserted into a 3/16" pre-punched hole and the pin is driven into the base, thereby expanding the rivet legs and locking the duct and sub-panel in place. The panel thickness (including the duct thickness) should be a maximum of 3/16".

<b>Short Description</b>	Panel Rivet, PA66, Natural, 1000/bag
<b>Global Part Name</b>	PR1-PA66-NA
<b>Technical Description</b>	Panel Rivet
<b>Minimum Tensile Strength (Imperial)</b>	107.0
<b>Minimum Tensile Strength (Metric)</b>	478
<b>Panel Thickness Min(Imperial)</b>	0.15
<b>Panel Thickness Max(Imperial)</b>	0.28
<b>Panel Thickness Min (Metric)</b>	3.9
<b>Panel Thickness Max (Metric)</b>	7.0
<b>Mounting Hole Diameter D (Imperial)</b>	0.2
<b>Mounting Hole Diameter D (Metric)</b>	5.0 mm
<b>Mounting Hole Diameter D Max (Metric)</b>	5.0
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 HB

**Halogen free** Yes

**Operating Temperature (Metric)** -40°F to +176°F (-40°C to +80°C)

**Reach Complaint(Article 33)** No

**ROHS Complaint** Yes

**Package Quantity(Imperial)** 1000

**Package Quantity (Metric)** 1000

**Customs Number** 3925900000