

## Specification Sheet

Part Number: PR1M4

Panel rivets are made with nylon material to hold duct securely to the panel without corroding, ensuring longevity.

Panel rivets can be easily inserted with use of a specially designed, long shafted panel rivet tool.

Ergonomic design of the tool ensures effortless use when inserting rivets into deep channels or locations difficult to access.



Panel Rivet, PA66, Natural, 1000/bag

Article Number 181-00139

Type PR1

Color Natural (NA)

Quantity Per EA

Product Description HellermannTyton panel rivets are one piece drive rivets that provide a fast, economic means of affixing wiring duct. The rivet is inserted into a 3/16" pre-punched hole and the pin is driven into the base, thereby expanding the rivet legs and locking the duct and sub-panel in place. The panel thickness (including the duct thickness) should be a maximum of 3/16".

Short Description Panel Rivet, PA66, Natural, 1000/bag

Global Part Name PR1-PA66-NA

Minimum Tensile Strength (Imperial) 107.0

Minimum Tensile Strength (Metric) 478

Panel Thickness Min (Imperial) 0.15

Panel Thickness Max (Imperial) 0.28

Panel Thickness Min (Metric) 3.9

Panel Thickness Max (Metric) 7.0

Mounting Hole Diameter D (Imperial) 0.2

Mounting Hole Diameter D (Metric) 5.0 mm

Mounting Hole Diameter D Max (Metric) 5.0

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL 94 HB

Halogen Free Yes

Operating Temperature -40°F to +176°F (-40°C to +80°C)

Reach Compliant (Article 33) No

ROHS Compliant Yes

Package Quantity (Imperial) 1000

Package Quantity (Metric) 1000

Customs Number 3926909988