

Specification Sheet

Part Number: 181-00222



Solid Wall Wiring Duct, 2.5" X 3", Adhesive, PVC, Gray, 120ft/Carton

Article Number 181-00222

Type SDA2.5X3

Color Gray (GY)

Features & Benefits

- Solid wall construction provides excellent coverage to keep wires clean.
- Durable material protects wires from damage, with long-lasting performance.
- Standard colors complement or contrast light and dark environments.
- Nonpermanent adhesive allows repositioning prior to final installation.
- Optional covers snap on and off easily, and their nonslip lining ensures they stay in place even under vibration.

Quantity Per carton

| | |
|---|---|
| Product Description | HellermannTyton Solid Wall Duct efficiently routes and protects wire. It is designed for straight wire runs where break-outs are not required. Manufactured from high impact, rigid PVC, it comes in six-foot lengths. Pressure-sensitive, rubber-based adhesive backing aids in temporary positioning. |
| Short Description | Solid Wall Wiring Duct, 2.5" X 3", Adhesive, PVC, Gray, 120ft/Carton |
| Global Part Name | SDA2.5X3-PVC-GY |
| Technical Description | Adhesive |
| Length L (Imperial) | 6.0 |
| Length L (Metric) | 1.83 |
| Width W (Imperial) | 2.5 |
| Width W (Metric) | 63.5 |
| Height H (Imperial) | 3.07 |
| Height H (Metric) | 77.9 |
| Mounting Hole Centers (Imperial) | 4.0 |
| Material | Polyvinylchloride (PVC) |
| Material Shortcut | PVC |

| | |
|--|--|
| Flammability | Self-Extinguishing |
| Halogen free | No |
| Operating Temperature (Metric) | +122°F (+50°C) |
| Reach Complaint(Article 33) | No |
| ROHS Complaint | Yes |
| Certification/Specification WEB | CSA EN 50085-2-3_1A EN 50085-1:2005 + A1:2013 UL |
| UL Recognized (US) | Yes |
| Package Quantity(Imperial) | 120 |
| Package Quantity (Metric) | 36.58 |