

## Specification Sheet

Part Number: 181-00470

Solid wall construction provides excellent coverage to keep wires clean.

Durable material protects wires from damage, with long-lasting performance.

Available standard colors complement or contrast in light and dark environments.

Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.



Solid Wall Wiring Duct, 3" x 1", Non-Adhesive, PVC, Black, 120ft/Carton

**Article Number** 181-00470

**Type** SD3X1

**Color** Black (BK)

**Quantity Per** carton

**Product Description** HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6-foot lengths.

|   |   |
|---|---|
| <b>Short Description</b>                | Solid Wall Wiring Duct, 3" x 1", Non-Adhesive, PVC, Black, 120ft/Carton |
| <b>Global Part Name</b>                 | SD3X1-PVC-BK  |
| <b>Technical Description</b>            | Non-Adhesive  |
| <b>Length L (Imperial)</b>              | 6.0   |
| <b>Length L (Metric)</b>                | 1.83  |
| <b>Fixation Method</b>                  | Non-Adhesive  |
| <b>Width W (Imperial)</b>               | 3.0   |
| <b>Width W (Metric)</b>                 | 76.2  |
| <b>Height H (Imperial)</b>              | 1.06  |
| <b>Height H (Metric)</b>                | 26.9  |
| <b>Mounting Hole Centers (Imperial)</b> | 4.0   |
| <b>Material</b>                         | Polyvinylchloride (PVC)   |
| <b>Material Shortcut</b>                | PVC   |
| <b>Flammability</b>                     | Self-Extinguishing  |

|                                     |  |
|-------------------------------------|--|
| <b>Halogen Free</b>                 | No   |
| <b>Operating Temperature</b>        | +122°F (+50°C)                                   |
| <b>Reach Compliant (Article 33)</b> | No   |
| <b>ROHS Compliant</b>               | Yes  |
| <b>Certification/Specification</b>  | EN 50085-1:2005 + A1:2013 CSA EN 50085-2-3_1A UL |
| <b>UL Recognized (US)</b>           | Yes  |
| <b>Package Quantity (Imperial)</b>  | 120  |
| <b>Package Quantity (Metric)</b>    | 36.58  |
| <b>Customs Number</b>               | 3925900000                                       |

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)