

## Specification Sheet

Part Number: 181-00504



Solid Wall Wiring Duct, 2" X 3", Adhesive, PVC, White, 120ft/Carton

**Article Number** 181-00504

**Type** SDA2X3

**Color** White (WH)

**Features & Benefits**

- Solid wall construction provides excellent coverage to keep wires clean.
- Durable material protects wires from damage, with long-lasting performance.
- Standard colors complement or contrast light and dark environments.
- Nonpermanent adhesive allows repositioning prior to final installation.
- Optional covers snap on and off easily, and their nonslip lining ensures they stay in place even under vibration.

**Quantity Per** carton

|   |   |
|---|---|
| <b>Product Description</b>              | HellermannTyton Solid Wall Duct efficiently routes and protects wire. It is designed for straight wire runs where break-outs are not required. Manufactured from high impact, rigid PVC, it comes in six-foot lengths. Pressure-sensitive, rubber-based adhesive backing aids in temporary positioning. |
| <b>Short Description</b>                | Solid Wall Wiring Duct, 2" X 3", Adhesive, PVC, White, 120ft/Carton   |
| <b>Global Part Name</b>                 | SDA2X3-PVC-WH   |
| <b>Technical Description</b>            | Adhesive  |
| <b>Length L (Imperial)</b>              | 6.0   |
| <b>Length L (Metric)</b>                | 1.83  |
| <b>Width W (Imperial)</b>               | 2.0   |
| <b>Width W (Metric)</b>                 | 50.8  |
| <b>Height H (Imperial)</b>              | 3.07  |
| <b>Height H (Metric)</b>                | 77.9  |
| <b>Mounting Hole Centers (Imperial)</b> | 4.0   |
| <b>Material</b>                         | Polyvinylchloride (PVC)   |
| <b>Material Shortcut</b>                | PVC   |

|  |  |
|--|--|
| <b>Flammability</b>                    | Self-Extinguishing                               |
| <b>Halogen free</b>                    | No   |
| <b>Operating Temperature (Metric)</b>  | +122°F (+50°C)                                   |
| <b>Reach Complaint(Article 33)</b>     | No   |
| <b>ROHS Complaint</b>                  | Yes  |
| <b>Certification/Specification WEB</b> | EN 50085-1:2005 + A1:2013 UL CSA EN 50085-2-3_1A |
| <b>UL Recognized (US)</b>              | Yes  |
| <b>Package Quantity(Imperial)</b>      | 120  |
| <b>Package Quantity (Metric)</b>       | 36.58  |