

## Specification Sheet

Part Number: 181-00515

Solid wall construction provides excellent coverage to keep wires clean.

Durable material protects wires from damage, with long-lasting performance.

Standard colors complement or contrast light and dark environments.

Nonpermanent adhesive allows repositioning prior to final installation.

Optional covers snap on and off easily, and their nonslip lining ensures they stay in place even under vibration.



Solid Wall Wiring Duct, 3" X 4", Adhesive, PVC, White, 120ft/Carton

**Article Number** 181-00515

**Type** SDA3X4

**Color** White (WH)

**Quantity Per** carton

**Product Description** HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct is designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6 foot lengths.

|   |   |
|---|---|
| <b>Short Description</b>                | Solid Wall Wiring Duct, 3" X 4", Adhesive, PVC, White, 120ft/Carton |
| <b>Global Part Name</b>                 | SDA3X4-PVC-WH   |
| <b>Technical Description</b>            | Adhesive  |
| <b>Length L (Imperial)</b>              | 6.0   |
| <b>Length L (Metric)</b>                | 1.83  |
| <b>Fixation Method</b>                  | Adhesive  |
| <b>Width W (Imperial)</b>               | 3.0   |
| <b>Width W (Metric)</b>                 | 76.2  |
| <b>Height H (Imperial)</b>              | 4.07  |
| <b>Height H (Metric)</b>                | 103.4   |
| <b>Mounting Hole Centers (Imperial)</b> | 4.0   |
| <b>Material</b>                         | Polyvinylchloride (PVC)   |
| <b>Material Shortcut</b>                | PVC   |
| <b>Flammability</b>                     | Self-Extinguishing  |

|                                     |  |
|-------------------------------------|--|
| <b>Halogen Free</b>                 | No   |
| <b>Operating Temperature</b>        | +122°F (+50°C)                                   |
| <b>Reach Compliant (Article 33)</b> | No   |
| <b>ROHS Compliant</b>               | Yes  |
| <b>Certification/Specification</b>  | EN 50085-1:2005 + A1:2013 UL EN 50085-2-3_1A CSA |
| <b>UL Recognized (US)</b>           | Yes  |
| <b>Package Quantity (Imperial)</b>  | 120  |
| <b>Package Quantity (Metric)</b>    | 36.58  |

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)