


## Specification Sheet

Part Number: 181-23020



Solid-Wall Wiring Duct, 2" x 2", Non-Adhesive, PVC, Intrinsic Blue, 120 ft/carton

Article Number	181-23020
Type	SD2X2
Color	Intrinsic Blue (IBU)
Features & Benefits	<ul style="list-style-type: none"><li>• Solid wall construction provides excellent coverage to keep wires clean.</li><li>• Durable material protects wires from damage, with long-lasting performance.</li><li>• Available standard colors complement or contrast in light and dark environments.</li><li>• Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.</li></ul>
Quantity Per	carton

### Product Description

HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire. Solid Wall wiring duct is designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6-foot lengths.

<b>Short Description</b>	Solid-Wall Wiring Duct, 2" x 2", Non-Adhesive, PVC, Intrinsic Blue, 120 ft/carton
<b>Global Part Name</b>	SD2X2-PVC-BU
<b>Length L (Imperial)</b>	6.0
<b>Length L (Metric)</b>	1.83
<b>Width W (Imperial)</b>	2.0
<b>Width W (Metric)</b>	50.8
<b>Height H (Imperial)</b>	2.07
<b>Height H (Metric)</b>	52.60
<b>Mounting Hole Centers (Imperial)</b>	4.0
<b>Material</b>	Polyvinylchloride (PVC)
<b>Material Shortcut</b>	PVC
<b>Flammability</b>	Self-Extinguishing
<b>Halogen free</b>	No
<b>Operating Temperature (Metric)</b>	+122°F (+50°C)
<b>Reach Complaint(Article 33)</b>	No

**ROHS Complaint**

Yes

**Certification/Specification WEB**

EN 50085-1:2005 + A1:2013 UL EN 50085-2-3\_1A CSA

**UL Recognized (US)**

Yes

**Package Quantity(Imperial)**

120

**Package Quantity (Metric)**

36.58