

## Specification Sheet

Part Number: 181-44013



Solid Wall Wiring Duct, 4" x 4", Non-Adhesive, PVC, White, 30ft/Box

**Article Number** 181-44013

**Type** SD4X4

**Color** White (WH)

**Features & Benefits**

- Solid wall construction provides excellent coverage to keep wires clean.
- Durable material protects wires from damage, with long-lasting performance.
- Available standard colors complement or contrast in light and dark environments.
- Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.

**Quantity Per** box

|   |  |
|---|--|
| <b>Product Description</b>              | HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6 foot lengths. |
| <b>Short Description</b>                | Solid Wall Wiring Duct, 4" x 4", Non-Adhesive, PVC, White, 30ft/Box  |
| <b>Global Part Name</b>                 | SD4X4-PVC-WH   |
| <b>Technical Description</b>            | Non-Adhesive   |
| <b>Length L (Imperial)</b>              | 6.0  |
| <b>Length L (Metric)</b>                | 1.83   |
| <b>Width W (Imperial)</b>               | 4.0  |
| <b>Width W (Metric)</b>                 | 101.6  |
| <b>Height H (Imperial)</b>              | 4.07   |
| <b>Height H (Metric)</b>                | 103.40   |
| <b>Mounting Hole Centers (Imperial)</b> | 4.0  |
| <b>Material</b>                         | Polyvinylchloride (PVC)  |
| <b>Material Shortcut</b>                | PVC  |

|  |  |
|--|--|
| <b>Flammability</b>                    | Self-Extinguishing                               |
| <b>Halogen free</b>                    | No   |
| <b>Operating Temperature (Metric)</b>  | +122°F (+50°C)                                   |
| <b>Reach Complaint(Article 33)</b>     | No   |
| <b>ROHS Complaint</b>                  | Yes  |
| <b>Certification/Specification WEB</b> | UL EN 50085-1:2005 + A1:2013 CSA EN 50085-2-3_1A |
| <b>UL Recognized (US)</b>              | Yes  |
| <b>Package Quantity(Imperial)</b>      | 30   |
| <b>Package Quantity (Metric)</b>       | 9.14   |
| <b>Customs Number</b>                  | 3925900000                                       |