


Specification Sheet

Part Number: 183-15075



Excellent fire-safety characteristics.

Narrow slots suitable for small-diameter wires.

Fingers can be removed with no sharp edges at pre-notched snap-off points.

Duct covers hold securely even in a vertical position and under vibration.

Halogen Free Slotted Wiring Duct, w/o Adhesive, 50mm x 75mm, PC/ABS, Gray RAL, 28 m/Box

Article Number

183-15075

Type

HTWD-HF-50X75

Color

Gray RAL 7035 (7035)

Quantity Per

box

Product Description

HellermannTyton HTWD-HF halogen-free ducts are used wherever there are high demands on personal or material safety, such as public transport, tunnels, escalators and data processing centers. Snap-on covers are included with corresponding duct sizes to ensure complete wire protection. Base perforation according to DIN EN 50085. Note: Halogen-free PC+ABS is not resistant to all oils and greases.

Short Description

Halogen Free Slotted Wiring Duct, w/o Adhesive, 50mm x 75mm, PC/ABS, Gray RAL, 28 m/Box

Global Part Name

HTWD-HF-50X75-PC/ABS-GY

Length L (Imperial)	6.56
Length L (Metric)	2
Fixation Method	Screw Mounting
Width W (Imperial)	1.97
Width W (Metric)	50
Height H (Imperial)	2.95
Height H (Metric)	75.0
Material	Acrylonitrile Butadiene Styrene alloyed with Polycarbonate (PC/ABS)
Material Shortcut	PC/ABS
Flammability	UL 94 V-0
Halogen Free	Yes
Operating Temperature	-13°F to +194°F (-25°C to +90°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes

Certification/Specification

RATP | NF F 16-101 DIN EN [45545-2] ISO11925

Package Quantity (Imperial)

91.9

Package Quantity (Metric)

28

Customs Number

3925900000

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)