

Specification Sheet

Part Number: 183-17550



Excellent fire-safety characteristics.

Narrow slots suitable for small-diameter wires.

Fingers can be removed with no sharp edges at pre-notched snap-off points.

Duct covers hold securely even in a vertical position and under vibration.

Halogen Free Slotted Wiring Duct, w/o Adhesive, 75mm x 50mm, PC/ABS, Gray RAL, 28 m/Box

Article Number	183-17550
Type	HTWD-HF-75X50
Color	Gray RAL 7035 (7035)
Quantity Per	box

Product Description

HellermannTyton HTWD-HF halogen-free ducts are used wherever there are high demands on personal or material safety, such as public transport, tunnels, escalators and data processing centers. Snap-on covers are included with corresponding duct sizes to ensure complete wire protection. Base perforation according to DIN EN 50085. Note: Halogen-free PC+ABS is not resistant to all oils and greases.

Short Description

Halogen Free Slotted Wiring Duct, w/o Adhesive, 75mm x 50mm, PC/ABS, Gray RAL, 28 m/Box

Global Part Name	HTWD-HF-75X50-PC/ABS-GY
Length L (Imperial)	6.56
Length L (Metric)	2
Fixation Method	Screw Mounting
Width W (Imperial)	2.95
Width W (Metric)	75
Height H (Imperial)	1.97
Height H (Metric)	50.0
Material	Acrylonitrile Butadiene Styrene alloyed with Polycarbonate (PC/ABS)
Material Shortcut	PC/ABS
Flammability	UL 94 V0
Halogen Free	Yes
Operating Temperature	-13°F to +194°F (-25°C to +90°C)
Reach Compliant (Article 33)	Yes

ROHS Compliant	Yes
Certification/Specification	DIN EN [45545-2] ISO11925 RATP NF F 16-101
Package Quantity (Imperial)	65.6
Package Quantity (Metric)	28
Customs Number	3925900000

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)