

## Specification Sheet

Part Number: 183-17575



Excellent fire-safety characteristics.

Narrow slots suitable for small-diameter wires.

Fingers can be removed with no sharp edges at pre-notched snap-off points.

Duct covers hold securely even in a vertical position and under vibration.

Halogen Free Slotted Wiring Duct, w/o Adhesive, 75mm x 75mm, PC/ABS, Gray RAL, 24 m/Box

|                       |                      |
|-----------------------|----------------------|
| <b>Article Number</b> | 183-17575            |
| <b>Type</b>           | HTWD-HF-75X75        |
| <b>Color</b>          | Gray RAL 7035 (7035) |
| <b>Quantity Per</b>   | box                  |

|                            |  |
|----------------------------|--|
| <b>Product Description</b> | HellermannTyton HTWD-HF halogen-free ducts are used wherever there are high demands on personal or material safety, such as public transport, tunnels, escalators and data processing centers. Snap-on covers are included with corresponding duct sizes to ensure complete wire protection. Base perforation according to DIN EN 50085. Note: Halogen-free PC+ABS is not resistant to all oils and greases. |
|----------------------------|--|

|                          |   |
|--------------------------|---|
| <b>Short Description</b> | Halogen Free Slotted Wiring Duct, w/o Adhesive, 75mm x 75mm, PC/ABS, Gray RAL, 24 m/Box |
|--------------------------|---|

|                                     |   |
|-------------------------------------|---|
| <b>Global Part Name</b>             | HTWD-HF-75X75-PC/ABS-GY   |
| <b>Length L (Imperial)</b>          | 6.56  |
| <b>Length L (Metric)</b>            | 2   |
| <b>Fixation Method</b>              | Screw Mounting  |
| <b>Width W (Imperial)</b>           | 2.95  |
| <b>Width W (Metric)</b>             | 75  |
| <b>Height H (Imperial)</b>          | 2.95  |
| <b>Height H (Metric)</b>            | 75.0  |
| <b>Material</b>                     | Acrylonitrile Butadiene Styrene alloyed with Polycarbonate (PC/ABS) |
| <b>Material Shortcut</b>            | PC/ABS  |
| <b>Flammability</b>                 | UL 94 V0  |
| <b>Halogen Free</b>                 | Yes   |
| <b>Operating Temperature</b>        | -13°F to +194°F (-25°C to +90°C)                                    |
| <b>Reach Compliant (Article 33)</b> | Yes   |

**ROHS Compliant** Yes

**Certification/Specification** RATP | NF F 16-101 ISO11925 DIN EN [45545-2]

**Package Quantity (Imperial)** 78.7

**Package Quantity (Metric)** 24

**Customs Number** 3925900000