


## Specification Sheet

Part Number: 183-21260



Narrow slots suitable for small-diameter wires.

Fingers can be removed with no sharp edges at pre-notched snap-off points.

Duct covers hold securely even in a vertical position and under vibration.

Base perforation according to DIN EN 50085.

Halogen Free Slotted Wiring Duct & Cover, w/o Adhesive, 120mm x 60mm, PC/ABS, Gray, 12 m/Box

**Article Number**

183-21260

**Type**

HTWD-HF-120X60

**Color**

Gray (GY)

**Quantity Per**

box

**Product Description**

HelaDuct HTWD-HF wiring duct is used to route and protect wires in control panels and switching systems where there are high demands on personal or material safety in case of fire, such as in public transport, tunnels, data processing centers or public buildings. Snap-on covers are included with corresponding duct sizes to ensure complete wire protection.

**Short Description**

Halogen Free Slotted Wiring Duct & Cover, w/o Adhesive, 120mm x 60mm, PC/ABS, Gray, 12 m/Box

<b>Global Part Name</b>	HTWD-HF-120X60-PC/ABS-GY
<b>Length L (Imperial)</b>	6.56
<b>Length L (Metric)</b>	2.0
<b>Fixation Method</b>	Screw Mounting
<b>Width W (Imperial)</b>	4.72
<b>Width W (Metric)</b>	120.0
<b>Height H (Imperial)</b>	2.36
<b>Height H (Metric)</b>	60.0
<b>Material</b>	Acrylonitrile Butadiene Styrene alloyed with Polycarbonate (PC/ABS)
<b>Material Shortcut</b>	PC/ABS
<b>Flammability</b>	UL 94 V0
<b>Halogen Free</b>	Yes
<b>Operating Temperature</b>	-13°F to +194°F (-25°C to +90°C)
<b>Reach Compliant (Article 33)</b>	Yes

<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	UL   ANSI/UL 1565 DIN EN [45545-2] UL   CAN/CSA-C22.2 no. 18.5 UL   ANSI/UL 746B
<b>Package Quantity (Imperial)</b>	39.4
<b>Package Quantity (Metric)</b>	12.0

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)