

## Specification Sheet

Part Number: 184-13005

Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.

Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.

Mounting holes are uniform in size and are offered every 2 inches to accommodate compact designs and ease installation.

Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.



High Density Slotted Wall Wiring Duct, 1" x 3", Non-Adhesive, PVC, Gray, 120ft/Carton

**Article Number** 184-13005

**Type** SLHD1X3

**Color** Gray (GY)

**Quantity Per** carton

**Product Description** HellermannTyton Pro-Duct High-Density, Slotted-Wall Wiring Duct features narrow fingers equaling a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

**Short Description** High Density Slotted Wall Wiring Duct, 1" x 3", Non-Adhesive, PVC, Gray, 120ft/Carton

**Global Part Name** SLHD1X3-PVC-GY

**Technical Description** Non-Adhesive

**Length L (Imperial)** 6.0

**Length L (Metric)** 1.83

**Fixation Method** Non-Adhesive

**Width W (Imperial)** 1.0

**Width W (Metric)** 25.4

**Height H (Imperial)** 3.07

**Height H (Metric)** 77.9

**Mounting Hole Centers (Imperial)** 2.0

**Material** Polyvinylchloride (PVC)

**Material Shortcut** PVC

**Flammability** Self-extinguishing

**Halogen Free** No

<b>Operating Temperature</b>	+122°F (+50°C)
<b>Reach Compliant (Article 33)</b>	No
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	EN 50085-2-3_1A CSA UL EN 50085-1:2005 + A1:2013
<b>UL Recognized (US)</b>	Yes
<b>Package Quantity (Imperial)</b>	120
<b>Package Quantity (Metric)</b>	36.58
<b>Customs Number</b>	3925900000

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)