

## Specification Sheet

Part Number: 184-33003

Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.

Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.

Mounting holes are uniform in size and are offered every 2 inches to accommodate compact designs and ease installation.

Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.



High Density Slotted Wall Wiring Duct, 3" x 3", Non-Adhesive, PVC, White, 30ft/Box

**Article Number** 184-33003

**Type** SLHD3X3

**Color** White (WH)

**Quantity Per** box

**Product Description** HellermannTyton High-Density Slotted Wall Wiring Duct features narrow fingers equaling a 2-to-1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

**Short Description** High Density Slotted Wall Wiring Duct, 3" x 3", Non-Adhesive, PVC, White, 30ft/Box

**Global Part Name** SLHD3X3-PVC-WH

**Technical Description** Non-Adhesive

**Length L (Imperial)** 6.0

**Length L (Metric)** 1.83

**Width W (Imperial)** 3.0

**Width W (Metric)** 76.2

**Height H (Imperial)** 3.07

**Height H (Metric)** 77.9

**Mounting Hole Centers (Imperial)** 2.0

**Material** Polyvinylchloride (PVC)

**Material Shortcut** PVC

**Flammability** Self-extinguishing

**Halogen Free** No

**Operating Temperature** +122°F (+50°C)

<b>Reach Compliant (Article 33)</b>	No
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	EN 50085-2-3_1A UL CSA EN 50085-1:2005 + A1:2013
<b>UL Recognized (US)</b>	Yes
<b>Package Quantity (Imperial)</b>	30
<b>Package Quantity (Metric)</b>	9.14
<b>Customs Number</b>	3925900000

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)