

Specification Sheet

Part Number: SNP33GHS0H4

Installation and removal can be five times faster than conventional clamps .
Heat stabilized material is suitable for high temperature applications.
Completely reusable .
Will not rust or corrode .
Safety engineered.
No protruding band or cluster.
Can be installed with hose in place .
One-hand installation for tight places.



Snapper Hose Clamp, 1.29"–1.59" Bundle Diameter, PA66GF13, Black, 500/pkg

Article Number 190-00148

Type SNP33

Color Black (BK)

Quantity Per bag

Product Description	<p>Snapper Hose Clamps are lightweight and corrosion-resistant. Manufactured from high-performance thermoplastic materials selected to work well in a variety of diverse environments. A quick ratchet closure provides for reduced assembly line time and allows for application after connection of the hose. Release is achieved by initiating opposed lateral movement of the ratchet ends. Heat stabilized materials are available for high-temperature, motor, and under-hood applications. Snappers are also stable in a wide variety of chemicals including salts, bases, alcohols, ethers, detergents, gasoline, lubricating oils, and greases. The Snapper is available in 32 standard sizes ranging from 1/4" to 4-1/2" ID. Snappers are manufactured in white polyacetal and black polyamide 6.6 glass filled impact modified heat stabilized material. Custom designed and different colored or shaped Snappers are available based upon applications and volume requirements.</p>
Short Description	Snapper Hose Clamp, 1.29"—1.59" Bundle Diameter, PA66GF13, Black, 500/pkg
Global Part Name	SNP33-PA66GF13-BK
Fixation Method	Plug-in mounting
Variant	Closed
Wall Thickness WT (Imperial)	.068
Wall Thickness WT (Metric)	1.717
Material	Polyamide 6.6 glass filled impact modified heat stabilized (PA66GF13%)
Material Shortcut	PA66GF13

Flammability	UL 94 HB
UV Resistant (Yes/No)	No
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)