

Specification Sheet

Part Number: SNP38GHS0K2



Snapper Hose Clamp, 1.61" - 1.90" Bundle Diameter, PA66GF13, Black, 50/pkg

Article Number 192-10380

Type SNP38

Color Black (BK)

Features & Benefits

- Designed for quick, ratcheted installation and can be released and reused.
- Heat stabilized material is suitable for high temperature applications.

Quantity Per bag

| | |
|---------------------------------------|--|
| Product Description | Snapper Hose Clamps are lightweight and corrosion-resistant. Manufactured from high-performance thermoplastic materials selected to work well in a variety of diverse environments. A quick ratchet closure provides for reduced assembly line time and allows for application after connection of the hose. Release is achieved by initiating opposed lateral movement of the ratchet ends. Heat stabilized materials are available for high-temperature, motor, and under-hood applications. Snappers are also stable in a wide variety of chemicals including salts, bases, alcohols, ethers, detergents, gasoline, lubricating oils, and greases. The Snapper is available in 32 standard sizes ranging from 1/4" to 4-1/2" ID. Snappers are manufactured in white polyacetal and black polyamide 6.6 glass filled impact modified heat stabilized material. Custom designed and different colored or shaped Snappers are available based upon applications and volume requirements. |
| Short Description | Snapper Hose Clamp, 1.61" - 1.90" Bundle Diameter, PA66GF13, Black, 50/pkg |
| Global Part Name | SNP38-PA66GF13-BK |
| Fixation Method | Plug-in mounting |
| Variant | Closed |
| Bundle Diameter Min (Imperial) | 1.61 |
| Bundle Diameter Min (Metric) | 41.0 |
| Bundle Diameter Max (Imperial) | 1.88 |
| Bundle Diameter Max (Metric) | 48.1 |
| Nominal Diameter (Imperial) | 1.75 |
| Nominal Diameter (Metric) | 45 |

| | |
|-------------------------------------|--|
| Wall Thickness WT (Imperial) | .069 |
| Wall Thickness WT (Metric) | 1.8 |
| Material | Polyamide 6.6 glass filled impact modified heat stabilized (PA66GF13%) |
| Material Shortcut | PA66GF13 |
| Flammability | UL 94 HB |
| UV Resistant (Yes/No) | No |
| Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 50 |
| Package Quantity (Metric) | 50 |
| Customs Number | 3926909988 |
| Weight (Metric) | 0.42 |

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)