

## Specification Sheet

Part Number: 211-60000



P-Clamp, 0.39" Wide, 0.13" Max Bundle Dia, 0.17" Mounting Hole Dia, PA66HS, Black, 100/pkg

**Article Number** 211-60000

**Type** H1P

**Color** Black (BK)

**Features & Benefits**

- P-Clamps easily guide and locate wire and cables up to 1" in diameter.
- Designed with a radius edge to prevent chafing and cutting into insulation.

**Quantity Per** bag

**Product Description** HellermannTyton P-Clamps easily guide and locate wires and cables. The clamps are designed with a radius edges to prevent chafing and cutting into insulation. Available sizes up to 1" bundle diameters.

<b>Short Description</b>	P-Clamp, 0.39" Wide, 0.13" Max Bundle Dia, 0.17" Mounting Hole Dia, PA66HS, Black, 100/pkg
<b>Global Part Name</b>	H1P-PA66HS-BK
<b>Fixation Method</b>	screw-hole
<b>Variant</b>	Closed
<b>Width W (Imperial)</b>	0.39
<b>Width W (Metric)</b>	10.0
<b>Bundle Diameter Max (Imperial)</b>	0.13
<b>Bundle Diameter Max (Metric)</b>	3.2
<b>Nominal Diameter (Imperial)</b>	0.13
<b>Nominal Diameter (Metric)</b>	3.2
<b>Wall Thickness WT (Imperial)</b>	0.031
<b>Wall Thickness WT (Metric)</b>	0.8
<b>Mounting Hole Diameter D (Imperial)</b>	0.17
<b>Mounting Hole Diameter D (Metric)</b>	4.2 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.17

**Mounting Hole Diameter D Max (Imperial)** 0.17

**Mounting Hole Diameter D Max (Metric)** 4.2

**Mounting Hole Centers (Imperial)** 0.33

**Material** Polyamide 6.6 heat stabilized (PA66HS)

**Material Shortcut** PA66HS

**Flammability** UL 94 V2

**UV Resistant (Yes/No)** No

**Operating Temperature (Metric)** -40°F to +221°F (-40°C to +105°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**Package Quantity(Imperial)** 100

**Package Quantity (Metric)** 100

**Customs Number** 3926909988

**Content Unit(BMEcat)** pcs.

**Weight (Metric)**

0.3

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)