

## Specification Sheet

Part Number: 211-60040



P-Clamps easily guide and locate wire and cables up to 1" in diameter. Designed with a radius edge to prevent chafing and cutting into insulation.

P-Clamp, 0.39" Wide, 0.26" Max Bundle Dia, 0.17" Mounting Hole Dia, PA66HS, Black, 1000/pkg

**Article Number** 211-60040

**Type** H3P

**Color** Black (BK)

**Quantity Per** bag

**Product Description** HellermannTyton P-Clamps easily guide and locate wires and cables. The clamps are designed with a radius edges to prevent chafing and cutting into insulation. Available sizes up to 1" bundle diameters.

**Short Description** P-Clamp, 0.39" Wide, 0.26" Max Bundle Dia, 0.17" Mounting Hole Dia, PA66HS, Black, 1000/pkg

**Global Part Name** H3P-PA66HS-BK

<b>Fixation Method</b>	screw-hole
<b>Variant</b>	Closed
<b>Width W (Imperial)</b>	0.39
<b>Width W (Metric)</b>	10.0
<b>Bundle Diameter Max (Imperial)</b>	0.26
<b>Bundle Diameter Max (Metric)</b>	6.5
<b>Nominal Diameter (Imperial)</b>	0.25
<b>Nominal Diameter (Metric)</b>	6.5
<b>Wall Thickness WT (Imperial)</b>	0.039
<b>Wall Thickness WT (Metric)</b>	1.0
<b>Mounting Hole Diameter D (Imperial)</b>	0.17
<b>Mounting Hole Diameter D (Metric)</b>	4.2 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.17
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.17
<b>Mounting Hole Diameter D Max (Metric)</b>	4.2
<b>Mounting Hole Centers (Imperial)</b>	0.39

**Material** Polyamide 6.6 heat stabilized (PA66HS)

**Material Shortcut** PA66HS

**Flammability** UL 94 V-2

**UV Resistant (Yes/No)** No

**Operating Temperature** -40°F to +221°F (-40°C to +105°C)

**ROHS Compliant** Yes

**Package Quantity (Imperial)** 1000

**Package Quantity (Metric)** 1000

**Customs Number** 3926909988