

## Specification Sheet

Part Number: 211-60049



P-Clamps easily guide and locate wire and cables up to 1" in diameter. Designed with a radius edge to prevent chafing and cutting into insulation.

P-Clamp, 0.39" Wide, 0.31" Max Bundle Dia, 0.17" Mounting Hole Dia, PA66, Natural, 1000/pkg

**Article Number** 211-60049

**Type** H4P

**Color** Natural (NA)

**Quantity Per** pcs.

**Product Description** HellermannTyton P-Clamps easily guide and locate wires and cables. The clamps are designed with a radius edges to prevent chafing and cutting into insulation. Available sizes up to 1" bundle diameters.

**Short Description** P-Clamp, 0.39" Wide, 0.31" Max Bundle Dia, 0.17" Mounting Hole Dia, PA66, Natural, 1000/pkg

**Global Part Name** H4P-PA66-NA

|  |            |
|--|------------|
| <b>Fixation Method</b>                         | screw-hole |
| <b>Variant</b>                                 | Closed     |
| <b>Width W (Imperial)</b>                      | 0.39       |
| <b>Width W (Metric)</b>                        | 10.0       |
| <b>Bundle Diameter Max (Imperial)</b>          | 0.31       |
| <b>Bundle Diameter Max (Metric)</b>            | 8.0        |
| <b>Nominal Diameter (Imperial)</b>             | 0.31       |
| <b>Nominal Diameter (Metric)</b>               | 8.0        |
| <b>Wall Thickness WT (Imperial)</b>            | 0.047      |
| <b>Wall Thickness WT (Metric)</b>              | 1.2        |
| <b>Mounting Hole Diameter D (Imperial)</b>     | 0.17       |
| <b>Mounting Hole Diameter D (Metric)</b>       | 4.2 mm     |
| <b>Mounting Hole Diameter D Min (Imperial)</b> | 0.17       |
| <b>Mounting Hole Diameter D Max (Imperial)</b> | 0.17       |
| <b>Mounting Hole Diameter D Max (Metric)</b>   | 4.2        |
| <b>Mounting Hole Centers (Imperial)</b>        | 0.39       |

|                                     |                                  |
|-------------------------------------|----------------------------------|
| <b>Material</b>                     | Polyamide 6.6 (PA66)             |
| <b>Material Shortcut</b>            | PA66                             |
| <b>Flammability</b>                 | UL 94 V-2                        |
| <b>UV Resistant (Yes/No)</b>        | No                               |
| <b>Operating Temperature</b>        | -40°F to +185°F (-40°C to +85°C) |
| <b>Reach Compliant (Article 33)</b> | Yes                              |
| <b>ROHS Compliant</b>               | Yes                              |
| <b>Certification/Specification</b>  | DIN EN [45545-2]                 |
| <b>Package Quantity (Imperial)</b>  | 1000                             |
| <b>Package Quantity (Metric)</b>    | 1000                             |
| <b>Customs Number</b>               | 3926909988                       |