

## Specification Sheet

Part Number: 211-60069



P-Clamp, 0.39" Wide, 0.43" Max Bundle Dia, 0.17" Mounting Hole Dia, PA66, Natural, 1000/pkg

**Article Number** 211-60069

**Type** H6P

**Color** Natural (NA)

**Features & Benefits**

- P-Clamps easily guide and locate wire and cables up to 1" in diameter.
- Designed with a radius edge to prevent chafing and cutting into insulation.

**Quantity Per** pcs.

**Product Description** HellermannTyton P-Clamps easily guide and locate wires and cables. The clamps are designed with a radius edges to prevent chafing and cutting into insulation. Available sizes up to 1" bundle diameters.

<b>Short Description</b>	P-Clamp, 0.39" Wide, 0.43" Max Bundle Dia, 0.17" Mounting Hole Dia, PA66, Natural, 1000/pkg
<b>Global Part Name</b>	H6P-PA66-NA
<b>Fixation Method</b>	screw-hole
<b>Variant</b>	Closed
<b>Width W (Imperial)</b>	0.39
<b>Width W (Metric)</b>	10.0
<b>Bundle Diameter Max (Imperial)</b>	0.43
<b>Bundle Diameter Max (Metric)</b>	11.0
<b>Nominal Diameter (Imperial)</b>	0.44
<b>Nominal Diameter (Metric)</b>	11.0
<b>Wall Thickness WT (Imperial)</b>	0.047
<b>Wall Thickness WT (Metric)</b>	1.2
<b>Mounting Hole Diameter D (Imperial)</b>	0.17
<b>Mounting Hole Diameter D (Metric)</b>	4.2 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.17

**Mounting Hole Diameter D Max (Imperial)** 0.17

**Mounting Hole Diameter D Max (Metric)** 4.2

**Mounting Hole Centers (Imperial)** 0.51

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Flammability** UL 94 V2

**UV Resistant (Yes/No)** No

**Operating Temperature (Metric)** -40°F to +185°F (-40°C to +85°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**Certification/Specification WEB** RATP | NF EN [45545-2]

**Package Quantity(Imperial)** 1000

**Package Quantity (Metric)** 1000

**Content Unit(BMEcat)** pcs.

**Weight (Metric)**

0.7

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)