

## Specification Sheet

Part Number: 211-60179



P-Clamp, 0.47" Wide, 1.24" Max Bundle Dia, 0.2" Mounting Hole Dia, PA66, Natural, 250/pkg

|                                |  |
|--------------------------------|--|
| <b>Article Number</b>          | 211-60179  |
| <b>Type</b>                    | H17P   |
| <b>Color</b>                   | Natural (NA)   |
| <b>Features &amp; Benefits</b> | <ul style="list-style-type: none"><li>• P-Clamps easily guide and locate wire and cables up to 1" in diameter.</li><li>• Designed with a radius edge to prevent chafing and cutting into insulation.</li></ul> |
| <b>Quantity Per</b>            | pcs.   |
| <b>Product Description</b>     | HellermannTyton P-Clamps easily guide and locate wires and cables. The clamps are designed with a radius edges to prevent chafing and cutting into insulation. Available sizes up to 1" bundle diameters.      |
| <b>Short Description</b>       | P-Clamp, 0.47" Wide, 1.24" Max Bundle Dia, 0.2" Mounting Hole Dia, PA66, Natural, 250/pkg  |

Global Part Name

H17P-PA66-NA

Fixation Method

screw-hole

Variant

Closed

Width W (Imperial)

0.47

Width W (Metric)

12.0

Bundle Diameter Max (Imperial)

1.24

Bundle Diameter Max (Metric)

31.5

Nominal Diameter (Imperial)

1-1/4

Nominal Diameter (Metric)

31.5

Wall Thickness WT (Imperial)

0.059

Wall Thickness WT (Metric)

1.5

Mounting Hole Diameter D (Imperial)

0.20

Mounting Hole Diameter D (Metric)

5.2 mm

Mounting Hole Diameter D Min (Imperial)

0.20

Mounting Hole Diameter D Max (Imperial)

0.20

Mounting Hole Diameter D Max (Metric)

5.2

Mounting Hole Centers (Imperial)

1.02

|  |                                  |
|--|----------------------------------|
| <b>Material</b>                        | Polyamide 6.6 (PA66)             |
| <b>Material Shortcut</b>               | PA66                             |
| <b>Flammability</b>                    | UL 94 V2                         |
| <b>UV Resistant (Yes/No)</b>           | No                               |
| <b>Operating Temperature (Metric)</b>  | -40°F to +185°F (-40°C to +85°C) |
| <b>Reach Complaint(Article 33)</b>     | Yes                              |
| <b>ROHS Complaint</b>                  | Yes                              |
| <b>Certification/Specification WEB</b> | RATP   NF EN [45545-2]           |
| <b>Package Quantity(Imperial)</b>      | 250                              |
| <b>Package Quantity (Metric)</b>       | 250                              |
| <b>Content Unit(BMEcat)</b>            | pcs.                             |
| <b>Weight (Metric)</b>                 | 2.26                             |

