

Specification Sheet

Part Number: MCRFW-B8

Raceway and fittings are manufactured from a UL94 V0 rated material to ensure compliance with codes.

All fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B and 569-A standard.

Raceway and fittings are UL Listed to 600 volts to meet new UL5A and CSA 22.2 No. 62-93 standards

Base is supplied with prepunched mounting slots every 8".

Raceway base includes adhesive double sided tape for aid in mounting. Raceway must still be properly fastened to the wall per instructions.



InfoStream Multi-Channel Raceway Base With Center Divider, 8 ft Long, PVC, Office White, 48 ft/pkg

Article Number	250-00003
Type	MCR-B8
Color	Office White (OEWH)
Quantity Per	box

Product Description	The InfoStream® multi-channel surface raceway system is designed to organize, protect and route multiple types of cable and wire along interior walls. Dividers snap inside raceway to create up to four channels to separate and route communication and power cables. Manufactured from lightweight PVC material, InfoStream multi-channel raceway components are UL5A listed and CSA 22.2 rated for up to 600 volts.
Short Description	InfoStream Multi-Channel Raceway Base With Center Divider, 8 ft Long, PVC, Office White, 48 ft/pkg
Global Part Name	MCR-B8-PVC-WH
Length L (Imperial)	8.0
Length L (Metric)	2.44
Width W (Imperial)	4.5
Width W (Metric)	114.3
Height H (Imperial)	2.05
Height H (Metric)	52.07
Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	UL 94 V0

Halogen Free	No
Operating Temperature	+122°F (+50°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
UL Listed (US and Canada)	Yes
UL Listed (US)	Yes
Package Quantity (Imperial)	48
Package Quantity (Metric)	14.63
Customs Number	3925900000

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)