

Specification Sheet


Part Number: MCRI-BS

Raceway and fittings are manufactured from a UL 94V-0 rated material to insure compliance with codes

All fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B and 569-A standard

Raceway and fittings are U.L. Listed to 600 Volts to meets new UL5A and CSA 22.2 No. 62-93 standards

Patented hinged cover speeds installation time by allowing installer to partially mount cover prior to laying cables



InfoStream Multi-Channel Raceway Base Splice, PVC, Ivory, 10/pkg

Article Number 250-00033

Type MCR-BS

Color Ivory (IV)

Quantity Per bag

Product Description HellermannTyton's InfoStream non-metallic raceway system can accommodate up to four separate channels of electrical, voice, data, video or fiber optic cabling. The elliptical shape is aesthetically pleasing when compared to other designs. The raceway's unique and patented design make installations quicker and easier.

Short Description	InfoStream Multi-Channel Raceway Base Splice, PVC, Ivory, 10/pkg
Global Part Name	MCR-BS-PVC-BGE
Width W (Imperial)	4.5
Width W (Metric)	114.3
Height H (Imperial)	2.05
Height H (Metric)	52.07
Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	UL 94 V0
Halogen Free	No
Operating Temperature	+122°F (+50°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
UL Listed (US and Canada)	Yes

UL Listed (US)	Yes
Package Quantity (Imperial)	10
Package Quantity (Metric)	10
Customs Number	3925900000