

Specification Sheet

Part Number: FHG



Grommet, Panel Thickness 0.319"-0.382", PA6, Natural, 82ft/pkg

Article Number 251-21709

Type G51NG

Color Natural (NA)

Features & Benefits

- Can be cut to length with scissors, eliminating waste and keeping stock to a minimum.
- Available in 9 sizes, for thicknesses from .016" to .512", insuring proper fit.

Quantity Per reel

Product Description

HellermannTyton's Flexiform grommet is a unique, continuous wire protection product which fits easily in all shapes and sizes of holes without the aid of tools or adhesives. Flexiform grommet can be used on any type of material including wood, steel, aluminum, plexiglass, and glass.

| | |
|---------------------------------------|--|
| Short Description | Grommet, Panel Thickness 0.319"-0.382", PA6, Natural, 82ft/pkg |
| Global Part Name | G51NG-PA6-NA |
| Length L (Imperial) | 82.0 |
| Variant | Open |
| Width W (Imperial) | 0.52 |
| Width W (Metric) | 13.2 |
| Height H (Imperial) | 0.268 |
| Height H (Metric) | 6.8 |
| Panel Thickness Min (Imperial) | 0.319 |
| Panel Thickness Max (Imperial) | 0.382 |
| Panel Thickness Min (Metric) | 8.10 |
| Panel Thickness Max (Metric) | 9.70 |
| Material | Polyamide 6 (PA6) |
| Material Shortcut | PA6 |

| | |
|-------------------------------------|----------------------------------|
| US MIL SPEC | MS21266-7N |
| Flammability | UL 94 HB |
| Halogen Free | Yes |
| Operating Temperature | -76°F to +203°F (-60°C to +95°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Certification/Specification | NASM21266 |
| Package Quantity (Imperial) | 82 |
| Package Quantity (Metric) | 25 |
| Customs Number | 3926909988 |
| Weight (Metric) | 1.185 |