

Specification Sheet

Part Number: 300-73601

Tubing is 2:1, thin wall and self extinguishing providing good resistance to common fluids and solvents.

Low shrink temperature gives excellent physical and electrical performance.

Available in multiple diameters and lengths offering several options to fit specific needs.



Heat Shrink Tubing, Non-Adh, 2:1 Shrink Ratio, .06" Supp/.03" Recov Dia, PO-X, Black, 1000ft/reel

Article Number 300-73601

Type TCN20-1.6/0.8

Color Black (BK)

Quantity Per box

Product Description TCN20 Heat Shrink is a general purpose, thin wall tubing used to protect electrical and mechanical wiring. Polyolefin material is self extinguishing and resistant against common fluids and solvents. The low shrink temperature and mechanical strength make this tubing widely used in the electric and electronics industry. Available in a wide range of diameters up to 2.0" (50.8mm) and multiple lengths. TCN20 Heat Shrink is UL224 125 °C 600V VW-1 and RoHS.

| | |
|-------------------------------------|--|
| Short Description | Heat Shrink Tubing, Non-Adh, 2:1 Shrink Ratio, .06" Supp/.03" Recov Dia, PO-X, Black, 1000ft/reel |
| Global Part Name | TCN20-1.6/0.8-PO-X-BK |
| Length L (Imperial) | 1000.0 |
| Length L (Metric) | 304.8 |
| Variant | Thin-Wall |
| Nominal Diameter (Imperial) | 0.06 |
| Nominal Diameter (Metric) | 1.6 |
| Wall Thickness WT (Imperial) | 0.013 |
| Wall Thickness WT (Metric) | 0.35 |
| Material | Polyolefin, cross-linked (PO-X) |
| Material Shortcut | PO-X |
| Flammability | Self-extinguishing UL 224 VW-1 |
| Halogen Free | No |
| Operating Temperature | -67°F to +257°F (-55°C to +125°C) |

| | |
|--------------------------------------|--|
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Certification/Specification | CSA C22.2 no. 198.1-06 UL 224 125 °C 600V VW-1 |
| UL Recognized (US) | Yes |
| UL Recognized (US and Canada) | Yes |
| Package Quantity (Imperial) | 1000 |
| Package Quantity (Metric) | 304.8 |
| Customs Number | 3926909988 |