

Specification Sheet

Part Number: 321-50013

Tubing is 3.5:1, thick wall adhesive lined.

Toughness and weatherability is ideal for low and medium voltage power applications.

Available in 3.28' (1.0 m) lengths, multiple diameters and 1 color (black).

Conveniently packed in a display carton.



Heat Shrink Tubing, 4' Long Stick, Thick Wall Adhesive Lined, Up to 3.5:1, 1.75", 45/12 dia, PO, Black, 4/pkg

Article Number

321-50013

Type

TREDUX HA47-48ST-45/12

Color

Black (BK)

Quantity Per

pcs.

Product Description

HA47 is a thick-wall adhesive lined heat shrink tubing for use in applications up to 1000 volts. The adhesive lining provides excellent moisture sealing and weather protection, making it suitable for above and below ground applications. Made of a polyolefin outer material, this tubing has a shrink ratio up to 3.5 to 1. The adhesive lining begins to activate as the temperature approaches 185° F (85° C).

Short Description

Heat Shrink Tubing, 4' Long Stick, Thick Wall Adhesive Lined, Up to 3.5:1, 1.75", 45/12 dia, PO, Black, 4/pkg

Global Part Name	TREDUX HA47-48ST-45/12-PO-X-BK
Length L (Imperial)	4.0
Length L (Metric)	1.0
Voltage Range	Low Voltage
Variant	Thick-Wall
Nominal Diameter (Imperial)	1.75
Nominal Diameter (Metric)	45
Wall Thickness WT (Imperial)	.161
Wall Thickness WT (Metric)	4.1
Material	Polyolefin, chemically cross-linked (PO-X)
Material Shortcut	PO-X
Adhesive	Hot melt adhesive
Flammability	Not flame retardant
Halogen Free	Yes

Operating Temperature -67°F to +230°F (-55°C to +110°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 4

Package Quantity (Metric) 4

Customs Number 3926909988

Weight (Imperial) 2.1