

## Specification Sheet

Part Number: 321-50015



Tubing is 3.5:1, thick wall adhesive lined.

Toughness and weatherability is ideal for low and medium voltage power applications.

Available in 3.28' (1.0 m) lengths, multiple diameters and 1 color (black).

Conveniently packed in a display carton.

Heat Shrink Tubing, 4' Long Stick, Thick Wall Adhesive Lined, Up to 3.5:1, 2.75", 68/22 dia, PO, Black, 1/pkg

**Article Number** 321-50015

**Type** TREDUX HA47-48ST-68/22

**Color** Black (BK)

**Quantity Per** pcs.

**Product Description** TREDUX HA47 thick wall heat shrink tubing has a adhesive liner that provides good moisture sealing and weather protection suitable for insulation and protection of low and medium voltage power applications. HA47 is tough and the weatherability makes it suitable for exposed applications and underground cable joints. Polyolefin material is pre-cut into 3.28' (1.0m) sticks and stored in a convenient display box. RoHS approved and Halogen free.

<b>Short Description</b>	Heat Shrink Tubing, 4' Long Stick, Thick Wall Adhesive Lined, Up to 3.5:1, 2.75", 68/22 dia, PO, Black, 1/pkg
<b>Global Part Name</b>	TREDUX HA47-48ST-68/22-PO-X-BK
<b>Length L (Imperial)</b>	4.0
<b>Length L (Metric)</b>	1.0
<b>Voltage Range</b>	Low and Medium Voltage
<b>Variant</b>	Thick-Wall
<b>Nominal Diameter (Imperial)</b>	2.75
<b>Nominal Diameter (Metric)</b>	68
<b>Wall Thickness WT (Imperial)</b>	.161
<b>Wall Thickness WT (Metric)</b>	4.1
<b>Material</b>	Polyolefin, chemically cross-linked (PO-X)
<b>Material Shortcut</b>	PO-X
<b>Adhesive</b>	Hot melt adhesive
<b>Flammability</b>	Not Flame Retardant

<b>Halogen Free</b>	Yes
<b>Operating Temperature</b>	-67°F to +230°F (-55°C to +110°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	1
<b>Package Quantity (Metric)</b>	1
<b>Customs Number</b>	3926909988
<b>Weight (Imperial)</b>	2.54