

Specification Sheet

Part Number: 321-50015



Heat Shrink Tubing, 4' Long Stick, Thick Wall Adhesive Lined, Up to 3.5:1, 2.75", 68/22 dia, PO, Black, 1/pkg

Article Number 321-50015

Type TREDUX HA47-48ST-68/22

Color Black (BK)

Features & Benefits

- Tubing is 3.5:1, thick wall adhesive lined.
- Toughness and weatherability is ideal for low and medium voltage power applications.
- Available in 3.28' (1.0 m) lengths, multiple diameters and 1 color (black).
- Conveniently packed in a display carton.

Quantity Per pcs.

Product Description	TREDUX HA47 thick wall heat shrink tubing has a adhesive liner that provides good moisture sealing and weather protection suitable for insulation and protection of low and medium voltage power applications. HA47 is tough and the weatherability makes it suitable for exposed applications and underground cable joints. Polyolefin material is pre-cut into 3.28' (1.0m) sticks and stored in a convenient display box. RoHS approved and Halogen free.
Short Description	Heat Shrink Tubing, 4' Long Stick, Thick Wall Adhesive Lined, Up to 3.5:1, 2.75", 68/22 dia, PO, Black, 1/pkg
Global Part Name	TREDUX HA47-48ST-68/22-PO-X-BK
Length L (Imperial)	4.0
Length L (Metric)	1.0
Voltage Range	Low and Medium Voltage
Variant	Thick-Wall
Nominal Diameter (Imperial)	2.75
Nominal Diameter (Metric)	68
Wall Thickness WT (Imperial)	.161
Wall Thickness WT (Metric)	4.1
Material	Polyolefin, chemically cross-linked (PO-X)

Material Shortcut	PO-X
Adhesive	Hot melt adhesive
Flammability	Not Flame Retardant
Halogen free	Yes
Operating Temperature (Metric)	-67°F to +230°F (-55°C to +110°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	1
Package Quantity (Metric)	1
Customs Number	3926909988
Weight (Metric)	1.15
Weight (Imperial)	2.54