


Specification Sheet

Part Number: 553-50016



Heat Shrink Labels, Single Side, Unslit, .25" (6.35mm), PO-X, White, 250/box

Article Number	553-50016
Type	HST6-2WH
Color	White (WH)
Features & Benefits	<ul style="list-style-type: none">• Slide Slit and optional center slits for easy wire insertion.• Smooth surface for clean and legible printing.• Supplied on a ladder style carrier so that markers can be kitted after printing.• A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.
Quantity Per	box

Product Description

HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production.

Short Description	Heat Shrink Labels, Single Side, Unslit, .25" (6.35mm), PO-X, White, 250/box
Global Part Name	HST6-2WH-PO-X-WH
Variant	Thin-Wall
Width W (Imperial)	1.9
Width W (Metric)	48.26
Thickness T (Imperial)	.003
Thickness T (Metric)	.0762
Height H (Imperial)	0.42
Height H (Metric)	10.67
Width of Liner (Metric)	76.2
Width of Liner (imperial)	3.0
Outside Diameter OD(Imperial)	0.25
Outside Diameter OD(metric)	6.35
Outside Diameter Max(Imperial)	0.25
Outside Diameter Max (metric)	6.35
Wall Thickness WT (Imperial)	0.028
Wall Thickness WT (Metric)	0.71

Material	Polyolefin, cross-linked (PO-X)
-----------------	---------------------------------

Material Shortcut PO-X

US MIL SPEC	SAE-AMS-DTL-23053/5 Class 1 and 3
--------------------	-----------------------------------

SAE-AS81531
MIL-STD-202G Method 215K

Flammability

UL 224 VW-1

Halogen free

No

Operating Temperature (Metric)

-67°F to +275°F (-55°C to +135°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

Certification/Specification WEB

SAE - AMS - DTL-23053/5 Class 1 and 3 UL 224 125 °C 600V VW-1 SAE - AS81531

Package Quantity(Imperial)	250
-----------------------------------	-----

Package Quantity (Metric) 250

Customs Number	3926909987
-----------------------	------------

Content Unit(BMEcat) pack

Labels per Column	1
Labels per Row	1
Weight (Metric)	0.362
Weight (Imperial)	0.79