


Specification Sheet

Part Number: 553-50083



ShrinkTrak Labels, 1-Sided, Unslit, .25" (6.35mm), Double Slit, PO-X, Yellow, 750/box

Article Number	553-50083
Type	HST6-2YE-2S
Color	Yellow (YE)
Features & Benefits	<ul style="list-style-type: none">• Slide Slit and optional center slits for easy wire insertion.• Smooth surface for clean and legible printing.• Supplied on a ladder style carrier so that markers can be kitted after printing.• A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.
Quantity Per	box

Product Description

HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production.

Short Description	ShrinkTrak Labels, 1-Sided, Unslit, .25" (6.35mm), Double Slit, PO-X, Yellow, 750/box
Global Part Name	HST6-2YE-2S-PO-X-YE
Variant	Thin-Wall
Width W (Imperial)	0.633
Width W (Metric)	16.08
Thickness T (Imperial)	.003
Thickness T (Metric)	.0762
Height H (Imperial)	0.42
Height H (Metric)	10.67
Width of Liner (Metric)	76.2
Width of Liner (imperial)	3.0
Outside Diameter OD(Imperial)	0.25
Outside Diameter OD(metric)	6.35
Outside Diameter Max(Imperial)	0.25
Outside Diameter Max (metric)	6.35
Wall Thickness WT (Imperial)	0.028

Wall Thickness WT (Metric)

0.71

Material

Polyolefin, cross-linked (PO-X)

Material Shortcut

PO-X

US MIL SPEC

SAE-AS81531

SAE-AMS-DTL-23053/5 Class 1 and 3
MIL-STD-202G Method 215K

Flammability

UL 224 VW-1

Halogen free

No

Operating Temperature (Metric)

-67°F to +275°F (-55°C to +135°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

Certification/Specification WEB

CEN SAE - AS81531 SAE - AMS - DTL-23053/5 Class 1 and 3

Package Quantity(Imperial)

750

Package Quantity (Metric)

750

Content Unit(BMEcat)

pack

Labels per Column

1

Labels per Row	3
Weight (Metric)	0.362
Weight (Imperial)	0.79