

Specification Sheet

Part Number: 553-50180



ShrinkTrak Labels, 1-Sided, 2-Slit, .125" (3.17mm), PO-X, Black, 750/box

Article Number

553-50180

Type

HST3-1BK-2S

Color

Black (BK)

Features & Benefits

- Slide Slit and optional center slits for easy wire insertion.
- Smooth surface for clean and legible printing.
- Supplied on a ladder style carrier so that markers can be kitted after printing.
- A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.

Quantity Per

reel

Product Description	HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production.
Short Description	ShrinkTrak Labels, 1-Sided, 2-Slit, .125" (3.17mm), PO-X, Black, 750/box
Global Part Name	HST3-1BK-2S-PO-X-BK
Variant	Thin-Wall
Width W (Imperial)	0.633
Width W (Metric)	16.08
Thickness T (Imperial)	.003
Thickness T (Metric)	.0762
Height H (Imperial)	0.6
Height H (Metric)	15.16
Width of Liner (Metric)	76.2
Width of Liner (imperial)	3.0
Outside Diameter OD(Imperial)	0.125
Outside Diameter OD(metric)	3.2

Outside Diameter Max(Imperial)	0.125
Outside Diameter Max (metric)	3.2
Wall Thickness WT (Imperial)	0.031
Wall Thickness WT (Metric)	0.79
Material	Polyolefin, cross-linked (PO-X)
Material Shortcut	PO-X
US MIL SPEC	MIL-STD-202G Method 215K SAE-AMS-DTL-23053/5 Class 1 and 3 SAE-AS81531
Flammability	UL 224 VW-1
Halogen free	No
Operating Temperature (Metric)	-67°F to +275°F (-55°C to +135°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	UL 224 125 °C 600V VW-1
Package Quantity(Imperial)	750

Package Quantity (Metric)	750
Content Unit(BMEcat)	pack
Weight (Metric)	0.294
Weight (Imperial)	16.08