

Specification Sheet

Part Number: 553-50199



ShrinkTrak Labels, 1-Sided, Unslit, .75" (19.05mm), PO-X, White, 2200/box

Article Number	553-50199
Type	HST18-6WH
Color	White (WH)
Features & Benefits	<p>Versatile •Flexible, flame retardant, heat shrinkable polyolefin tubing meets all military specification. •3:1 shrink ratio enables a wide range of wire sizes to be covered. •Standard colors - yellow, white and black. •Larger pack options result in less box changes. High Performance Design •Center slit and multiple slit versions reduce or eliminate hand cutting. •Nonslip printable liner allows additional marker data to be printed on the reverse side for records and placement instructions. •Use HellermannTyton's Durattach ribbon system for the highest print performance on the market. Reduce Printer Jams •Custom box opening allows markers to dispense directly into HellermannTyton thermal transfer printers. •Dispense markers faster and easier with waxed core dispenser.</p>
Quantity Per	box

Product Description

HellermannTyton's ShrinkTrak™ heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production.

Short Description

ShrinkTrak Labels, 1-Sided, Unslit, .75" (19.05mm), PO-X, White, 2200/box

Global Part Name

HST18-6WH-PO-X-WH

Variant

Thin-Wall

Width W (Imperial)

1.9

Width W (Metric)

48.26

Thickness T (Imperial)

.003

Thickness T (Metric)

.0762

Height H (Imperial)

0.6

Height H (Metric)

15.16

Width of Liner (Metric)

76.2

Width of Liner (imperial)

3.0

Outside Diameter Max(Imperial)

0.75

Outside Diameter Max (metric)

19.05

Wall Thickness WT (Imperial)

0.036

Wall Thickness WT (Metric)

0.91

Material

Polyolefin, cross-linked (PO-X)

Material Shortcut

PO-X

US MIL SPEC

SAE-AS81531

SAE-AMS-DTL-23053/5 Class 1 and 3
MIL-STD-202G Method 215K

Flammability

UL 224 VW-1

Halogen free

No

Operating Temperature (Metric)

-67°F to +275°F (-55°C to +135°C)

ROHS Complaint

Yes

Certification/Specification WEB

UL 224 125 °C 600V VW-1

Package Quantity(Imperial)

2200

Package Quantity (Metric)

2200

Weight (Metric)

5.98

Weight (Imperial)

13.02

© 2019 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)