

Specification Sheet

Part Number: 553-60001



Halogen free, for low smoke propagation, density and toxicity.
50 mm, 25 mm and 16 mm pre-cut marker options as standard, for ability to get multiple labels out of one tag.

Delivery in convenient storage boxes for protection.

ShrinkTrak Labels, 2-Sided, Unslit, Halogen Free, 1.97" x .24", Polyolefin, White, 5000/pkg

Article Number	553-60001
Type	TLFX32DS-1x50WH
Color	White (WH)
Quantity Per	carton

Product Description	<p>ShrinkTrak DS is a halogen-free, double-sided heat shrinkable marker with a 2:1 shrink ratio. HellermannTyton's unique ladder-style design assists in removing markers off the carrier. The side slits have been designed to ensure the wire entry gap is as large as possible while remaining on the carrier strip, enabling the user to quickly insert wire and cable into the marker. For a complete labeling solution, ShrinkTrak DS can be printed using HellermannTyton's TagPrint® Pro professional label creation software and thermal transfer printers. For double-sided printing, HellermannTyton's TrakMark DS double-sided printer produces excellent results. Choose among multiple ribbon types to create a permanent print that resists most solvents when shrunk and applied.</p>
Short Description	<p>ShrinkTrak Labels, 2-Sided, Unslit, Halogen Free, 1.97" x .24", Polyolefin, White, 5000/pkg</p>
Global Part Name	<p>TLFX32DS-1x50WH-PO-X-WH</p>
Length L (Imperial)	<p>2.0</p>
Length L (Metric)	<p>50.0</p>
Fixation Method	<p>Suspend</p>
Variant	<p>Roller form</p>
Width W (Imperial)	<p>2.0</p>
Width W (Metric)	<p>50.0</p>
Thickness T (Imperial)	<p>.0130</p>
Thickness T (Metric)	<p>.29</p>
Height H (Imperial)	<p>0.23</p>

Height H (Metric)	6.0
Width of Liner (Metric)	88.9
Width of Liner (Imperial)	3.50
Outside Diameter Max (Imperial)	0.12
Outside Diameter Max (Metric)	3.04
Wall Thickness WT (Imperial)	0.025
Wall Thickness WT (Metric)	0.635
Material	Polyolefin, cross-linked (PO-X)
Material Shortcut	PO-X
US MIL SPEC	MIL-STD-202J SAE AS5942 3.4.1
Flammability	UL 224 Halogen-free Low smoke generation Limited fire hazard Low generation of toxic gases and corrosive acid
Halogen Free	Yes
Operating Temperature	-67°F to +221°F (-55°C to +105°C)
Reach Compliant (Article 33)	Yes

ROHS Compliant	Yes
Certification/Specification	Exova NFPA130: 2017 DIN EN [45545-2] ASTM E 662 ASTM E 162 ASTM 1354
Package Quantity (Imperial)	5000
Package Quantity (Metric)	5000
Customs Number	3926909988

© 2022 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)