

Specification Sheet

Part Number: 553-60027



ShrinkTrak Labels, 2-Sided, 1-Slit, Halogen Free, .98" x 1.69", Polyolefin, White, 2,000/pkg

Article Number

553-60027

Type

TLFX254DS-2x25WH

Color

White (WH)

Features & Benefits

- Halogen Free, for low smoke propagation, density and toxicity.
- 50 mm, 25 mm and 16 mm pre-cut marker options as standard, for ability to get multiple labels out of one tag.
- Delivery in convenient storage boxes for protection.

Quantity Per

pack

Product Description

HellermannTyton's ShrinkTrak 3:1 ratio heat shrinkable markers make it easy to identify wire and cable. The ladder-style function has been designed to enhance the user's ability to pick markers off the carrier. The side slits have been specifically designed to ensure that the wire entry gap is as large as possible whilst remaining on the carrier strip. This enables the user to quickly insert wire and cable into the marker. For a complete labelling solution, ShrinkTrak can be printed using HellermannTyton's TagPrint Pro professional label creation software, thermal transfer printers and ribbons to create a permanent print which is resistant to most solvents when shrunk and applied.

Short Description

ShrinkTrak Labels, 2-Sided, 1-Slit, Halogen Free, .98" x 1.69", Polyolefin, White, 2,000/pkg

Global Part Name

TLFX254DS-2x25WH-PO-X-WH

Length L (Imperial)

1.0

Length L (Metric)

25.0

Fixation Method

Others

Variant

Thin-Wall

Width W (Imperial)

1.0

Width W (Metric)

25.0

Thickness T (Imperial)

.0130

Thickness T (Metric)

.29

Height H (Imperial)

1.69

Height H (Metric)

43.0

Width of Liner (Metric)

88.9

Width of Liner (imperial) 3.50

Outside Diameter Max(Imperial) 1.0

Outside Diameter Max (metric) 25.4

Wall Thickness WT (Imperial) 0.036

Wall Thickness WT (Metric) 0.925

Material Polyolefin, cross-linked (PO-X)

Material Shortcut PO-X

US MIL SPEC MIL-STD-202J

SAE AS5942 3.4.1

Flammability

UL 224

Halogen free

Yes

Operating Temperature (Metric)

-67°F to +221°F (-55°C to +105°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

Certification/Specification WEB

RST LAB | DIN 54837 (12/2007) ASTM E 662 RATP | NF F 16-101 BS-EN
ISO 4589-2 BS-6853:1999 EN ISO 11925-2: 2010 SAE AS5942 3.4.1 UNI CEI
11170-3

Package Quantity(Imperial)	2000
Package Quantity (Metric)	2000
Customs Number	3926909988
Content Unit(BMEcat)	pack
Weight (Metric)	2.9
Weight (Imperial)	6.39