

Specification Sheet

Part Number: 553-60028



ShrinkTrak Labels, 2-Sided, 1-Slit, Halogen Free, .98" x 2.48", Polyolefin, White, 1,000/pkg

Article Number

553-60028

Type

TLFX381DS-2x25WH

Color

White (WH)

Features & Benefits

- Halogen Free, for low smoke propagation, density and toxicity.
- 50 mm, 25 mm and 16 mm pre-cut marker options as standard, for ability to get multiple labels out of one tag.
- Delivery in convenient storage boxes for protection.

Quantity Per

pack

Product Description

HellermannTyton's ShrinkTrak 3:1 ratio heat shrinkable markers make it easy to identify wire and cable. The ladder-style function has been designed to enhance the user's ability to pick markers off the carrier. The side slits have been specifically designed to ensure that the wire entry gap is as large as possible whilst remaining on the carrier strip. This enables the user to quickly insert wire and cable into the marker. For a complete labelling solution, ShrinkTrak can be printed using HellermannTyton's TagPrint Pro professional label creation software, thermal transfer printers and ribbons to create a permanent print which is resistant to most solvents when shrunk and applied.

Short Description

ShrinkTrak Labels, 2-Sided, 1-Slit, Halogen Free, .98" x 2.48", Polyolefin, White, 1,000/pkg

Global Part Name

TLFX381DS-2x25WH-PO-X-WH

Length L (Imperial)

1.0

Length L (Metric)

25.0

Fixation Method

Others

Variant

Thin-Wall

Width W (Imperial)

1.0

Width W (Metric)

25.0

Thickness T (Imperial)

.0130

Thickness T (Metric)

.29

Height H (Imperial)

3.0

Height H (Metric)

76.2

Width of Liner (Metric)

88.9

Width of Liner (imperial) 3.50

Outside Diameter Max(Imperial) 1.5

Outside Diameter Max (metric) 38.1

Wall Thickness WT (Imperial) 0.038

Wall Thickness WT (Metric) 0.975

Material Polyolefin, cross-linked (PO-X)

Material Shortcut PO-X

US MIL SPEC SAE AS5942 3.4.1

MIL-STD-202J

Flammability

UL 224

Halogen free

Yes

Operating Temperature (Metric)

-67°F to +221°F (-55°C to +105°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

Certification/Specification WEB

ASTM E 662 EN ISO 11925-2: 2010 RATP | NF F 16-101 BS-EN ISO 4589-2
BS-6853:1999 SAE AS5942 3.4.1 UNI CEI 11170-3 RST LAB | DIN 54837
(12/2007)

Package Quantity(Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909988
Content Unit(BMEcat)	pack
Weight (Metric)	2.9
Weight (Imperial)	6.39