

## Specification Sheet

Part Number: 553-60040



ShrinkTrak Labels, 2-Sided, 2-Slit, Halogen Free, 0.63" x .24", Polyolefin, White, 15,000/pkg

**Article Number**

553-60040

**Type**

TLFX32DS-3x16WH

**Color**

White (WH)

**Features & Benefits**

- Halogen Free, for low smoke propagation, density and toxicity.
- 50 mm, 25 mm and 16 mm pre-cut marker options as standard, for ability to get multiple labels out of one tag.
- Delivery in convenient storage boxes for protection.

**Quantity Per**

pack

**Product Description**

HellermannTyton's ShrinkTrak 3:1 ratio heat shrinkable markers make it easy to identify wire and cable. The ladder-style function has been designed to enhance the user's ability to pick markers off the carrier. The side slits have been specifically designed to ensure that the wire entry gap is as large as possible whilst remaining on the carrier strip. This enables the user to quickly insert wire and cable into the marker. For a complete labelling solution, ShrinkTrak can be printed using HellermannTyton's TagPrint Pro professional label creation software, thermal transfer printers and ribbons to create a permanent print which is resistant to most solvents when shrunk and applied.

**Short Description**

ShrinkTrak Labels, 2-Sided, 2-Slit, Halogen Free, 0.63" x .24", Polyolefin, White, 15,000/pkg

**Global Part Name**

TLFX32DS-3x16WH-PO-X-WH

**Length L (Imperial)**

0.63

**Length L (Metric)**

16.0

**Fixation Method**

Others

**Variant**

Thin-Wall

**Width W (Imperial)**

0.63

**Width W (Metric)**

16.0

**Thickness T (Imperial)**

.0130

**Thickness T (Metric)**

.29

**Height H (Imperial)**

0.23

**Height H (Metric)**

6.0

**Width of Liner (Metric)**

88.9

**Width of Liner (imperial)** 3.50

**Outside Diameter Max(Imperial)** 0.12

**Outside Diameter Max (metric)** 3.04

**Wall Thickness WT (Imperial)** 0.025

**Wall Thickness WT (Metric)** 0.635

**Material** Polyolefin, cross-linked (PO-X)

**Material Shortcut** PO-X

**US MIL SPEC** SAE AS5942 3.4.1

MIL-STD-202J

**Flammability**

UL 224

**Halogen free**

Yes

**Operating Temperature (Metric)**

-67°F to +221°F (-55°C to +105°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**Certification/Specification WEB**

RST LAB | DIN 54837 (12/2007) BS-6853:1999 BS-EN ISO 4589-2 EN ISO 11925-2: 2010 SAE AS5942 3.4.1 ASTM E 662 UNI CEI 11170-3 RATP | NF F 16-101

<b>Package Quantity(Imperial)</b>	15000
<b>Package Quantity (Metric)</b>	15000
<b>Customs Number</b>	3926909988
<b>Content Unit(BMEcat)</b>	pack
<b>Weight (Metric)</b>	2.9
<b>Weight (Imperial)</b>	6.39