

Specification Sheet

Part Number: 553-60046



Halogen free, for low smoke propagation, density and toxicity.
50 mm, 25 mm and 16 mm pre-cut marker options as standard, for ability to get multiple labels out of one tag.

Delivery in convenient storage boxes for protection.

ShrinkTrak Labels, 2-Sided, 2-Slit, Halogen Free, 0.63" x 0.63", Polyolefin, White, 7,500/pkg

Article Number	553-60046
Type	TLFX95DS-3x16WH
Color	White (WH)
Quantity Per	carton

Product Description	<p>ShrinkTrak DS is a halogen-free, double-sided heat shrinkable marker with a 2:1 shrink ratio. HellermannTyton's unique ladder-style design assists in removing markers off the carrier. The side slits have been designed to ensure the wire entry gap is as large as possible while remaining on the carrier strip, enabling the user to quickly insert wire and cable into the marker. For a complete labeling solution, ShrinkTrak DS can be printed using HellermannTyton's TagPrint® Pro professional label creation software and thermal transfer printers. For double-sided printing, HellermannTyton's TrakMark DS double-sided printer produces excellent results. Choose among multiple ribbon types to create a permanent print that resists most solvents when shrunk and applied.</p>
Short Description	<p>ShrinkTrak Labels, 2-Sided, 2-Slit, Halogen Free, 0.63" x 0.63", Polyolefin, White, 7,500/pkg</p>
Global Part Name	<p>TLFX95DS-3x16WH-PO-X-WH</p>
Length L (Imperial)	<p>0.63</p>
Length L (Metric)	<p>16.0</p>
Fixation Method	<p>Suspend</p>
Variant	<p>Roller form</p>
Width W (Imperial)	<p>0.63</p>
Width W (Metric)	<p>16.0</p>
Thickness T (Imperial)	<p>.0130</p>
Thickness T (Metric)	<p>.29</p>
Height H (Imperial)	<p>0.62</p>

Height H (Metric)	16.0
Width of Liner (Metric)	88.9
Width of Liner (Imperial)	3.50
Outside Diameter Max (Imperial)	0.37
Outside Diameter Max (Metric)	9.39
Wall Thickness WT (Imperial)	0.028
Wall Thickness WT (Metric)	0.700
Material	Polyolefin, cross-linked (PO-X)
Material Shortcut	PO-X
US MIL SPEC	MIL-STD-202J SAE AS5942 3.4.1
Flammability	Limited fire hazard Low smoke generation Halogen-free Low generation of toxic gases and corrosive acid UL 224
Halogen Free	Yes
Operating Temperature	-67°F to +221°F (-55°C to +105°C)
Reach Compliant (Article 33)	Yes

ROHS Compliant	Yes
Certification/Specification	ASTM E 662 ASTM 1354 DIN EN [45545-2] ASTM E 162
Package Quantity (Imperial)	7500
Package Quantity (Metric)	7500
Customs Number	3926909988

© 2022 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)