

Specification Sheet

Part Number: 553-60128



ShrinkTrak Labels, 2-Sided, Unslit, Halogen Free, 0.63" x .87", Polyolefin, White, 500/pkg

Article Number

553-60128

Type

TLFX127DS-1X50WH

Color

White (WH)

Features & Benefits

- Halogen Free, for low smoke propagation, density and toxicity.
- 50 mm, 25 mm and 16 mm pre-cut marker options as standard, for ability to get multiple labels out of one tag.
- Delivery in convenient storage boxes for protection.

Quantity Per

box

Product Description

HellermannTyton's ShrinkTrak 3:1 ratio heat shrinkable markers make it easy to identify wire and cable. The ladder-style function has been designed to enhance the user's ability to pick markers off the carrier. The side slits have been specifically designed to ensure that the wire entry gap is as large as possible whilst remaining on the carrier strip. This enables the user to quickly insert wire and cable into the marker. For a complete labelling solution, ShrinkTrak can be printed using HellermannTyton's TagPrint Pro professional label creation software, thermal transfer printers and ribbons to create a permanent print which is resistant to most solvents when shrunk and applied.

Short Description

ShrinkTrak Labels, 2-Sided, Unslit, Halogen Free, 0.63" x .87", Polyolefin, White, 500/pkg

Global Part Name

TLFX127DS-1X50WH-PO-X-WH

Length L (Imperial)

0.63

Length L (Metric)

16.0

Fixation Method

Others

Variant

Thin-Wall

Width W (Imperial)

2.0

Width W (Metric)

50.0

Thickness T (Imperial)

.0130

Thickness T (Metric)

.29

Height H (Imperial)

0.86

Height H (Metric)

22.0

Width of Liner (Metric)

88.9

Width of Liner (imperial) 3.50

Outside Diameter Max(Imperial) 0.5

Outside Diameter Max (metric) 12.7

Wall Thickness WT (Imperial) 0.028

Wall Thickness WT (Metric) 0.700

Material Polyolefin, cross-linked (PO-X)

Material Shortcut PO-X

US MIL SPEC MIL-STD-202J

SAE AS5942 3.4.1

Flammability

UL 224

Halogen free

Yes

Operating Temperature (Metric)

-67°F to +221°F (-55°C to +105°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

Certification/Specification WEB

RATP | NF F 16-101 RST LAB | DIN 54837 (12/2007) BS-EN ISO 4589-2 EN ISO 11925-2: 2010 UNI CEI 11170-3 SAE AS5942 3.4.1 ASTM E 662 BS-6853:1999

Package Quantity(Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988
Content Unit(BMEcat)	pcs.
Weight (Metric)	.630
Weight (Imperial)	1.38