

Specification Sheet

Part Number: 556-04037



TT4030 Thermal Transfer Printer, 300 dpi, Gray, 1/pkg

Article Number 556-04037

Type TT4030

Color Gray (GY)

Features & Benefits

- Prints detectable TipTag markers, as well as thermal transfer labels and more, for use in food, beverage and pharmaceutical operations.
- High-volume, ultra-fast, premium-quality printing for dependable performance and excellent results.
- Color LCD touchscreen for intuitive control.
- Optional premium quality accessories such as a perforator and cutter extend the printer's capability.

Quantity Per EA

| | |
|----------------------------|--|
| Product Description | HellermannTyton's TT4030 Series thermal transfer printers are designed for high-volume, industrial-grade printing of thermal transfer labels and ShrinkTrak. Their user-friendly design features an informative display for simple navigation and instructional videos. The built-in caddy allows even the largest label rolls to fit inside, and the cutter can cut through the thickest material. The TT4030's print head delivers excellent results. This printer handles all sizes of HellermannTyton's ShrinkTrak markers and can print on even the smallest labels. Use with HellermannTyton's TagPrint Pro label printing software. |
| Short Description | TT4030 Thermal Transfer Printer, 300 dpi, Gray, 1/pkg |
| Global Part Name | TT4030-MET-GY |
| Length L (Imperial) | 15.0 |
| Length L (Metric) | 381.0 |
| Width W (Imperial) | 9.21 |
| Width W (Metric) | 252 |
| Height H (Imperial) | 11.34 |
| Height H (Metric) | 288 |
| Depth D (Imperial) | 18.11 |
| Depth D (Metric) | 460 |
| Power Supply | 100-240V / 50-60Hz |

| | |
|-------------------------------------|--|
| Material | Metal (MET) |
| Material Shortcut | MET |
| Halogen Free | No |
| Operating Temperature | +40°F to +104°F (+4°C to +40°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Certification/Specification | iLab CE 2014/35/EU iLab DIN EN 61000-6-2 rectification 1:2011-06 iLab IEC 60950-1 (ed.2) iLab IEC 60950-1 (ed.2);am1 iLab DIN EN 61000-6-2:2006-03 iLab IEC 60950-1 (ed.2);am2 CE 2014/35/EU iLab DIN EN 55032:2012-12 CE 2011/65/EU iLab EN 61000-6-2 iLab DIN EN 55032 rectification 1:2013-04 iLab DIN EN 55032:2016-02 iLab EN 61000-3-2 |
| Package Quantity (Imperial) | 1 |
| Package Quantity (Metric) | 1 |
| Customs Number | 8443913000 |
| Weight (Metric) | 9.98 |
| Weight (Imperial) | 22.021 |

