

Specification Sheet

Part Number: 556-04037



TT4030 Thermal Transfer Printer, 300 dpi, Gray, 1/pkg

Article Number

556-04037

Type

TT4030

Color

Gray (GY)

Features & Benefits

- Premium-quality printer is designed for medium- and heavy-duty industrial applications.
- Print accuracy, consistency, speed and power are best in class.
- 300 dpi print head fulfills all standard requirements for printing bar codes, warning signs, logos, and written information.
- Easily prints high-definition graphics such as 2D barcodes, standard bar codes, numbers, and text on adhesive labels, thermo plastics such as heat shrink and Tiptags.
- Print speeds up to 11.8 in (300 mm) per second are possible depending on the material being printed.
- Standard adjustments are made with the on-board tool, minimizing operator down time.
- The exceptionally durable print head is has a warranty of 24 months or 31 mi (50 km), whichever comes first, in thermal transfer mode.
- Optional premium quality accessories are designed to work seamlessly with the printer and will suit the most demanding needs.

Quantity Per

EA

Product Description

HellermannTyton's TT4030 Series thermal transfer printers are designed for high-volume, industrial-grade printing of thermal transfer labels and ShrinkTrak. Their user-friendly design features an informative display for simple navigation and instructional videos. The built-in caddy allows even the largest label rolls to fit inside, and the cutter can cut through the thickest material. The TT4030's print head delivers excellent results. This printer handles all sizes of HellermannTyton's ShrinkTrak markers and can print on even the smallest labels. Use with HellermannTyton's TagPrint Pro label printing software.

Short Description

TT4030 Thermal Transfer Printer, 300 dpi, Gray, 1/pkg

Global Part Name

TT4030-MET-GY

Length L (Imperial)

15.0

Length L (Metric)

381.0

Width W (Imperial)

9.21

Width W (Metric)

252

Height H (Imperial)

11.34

Height H (Metric)

288

Depth D (imperial)

18.11

Depth D (metric)

460

Material

Metal (MET)

Material Shortcut

MET

Halogen free	Yes
Operating Temperature (Metric)	+40°F to +104°F (+4°C to +40°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	iLab DIN EN 61000-6-2:2006-03 CE 2014/35/EU iLab EN 61000-6-2 iLab DIN EN 55032:2012-12 iLab DIN EN 55032 Berichtigung 1:2013-04 CE 2011/65/EU iLab DIN EN 55032:2016-02 iLab CE 2014/35/EU iLab IEC 60950-1 (ed.2);am1 iLab DIN EN 61000-6-2 Berichtigung 1:2011-06 iLab IEC 60950-1 (ed.2) iLab EN 61000-3-2 iLab IEC 60950-1 (ed.2);am2
Package Quantity(Imperial)	1
Package Quantity (Metric)	1
Content Unit(BMEcat)	pcs.
Weight (Metric)	9.98
Weight (Imperial)	22.021