

## Specification Sheet

Part Number: 558-00313



Adhesive Labels, Solid Color Continuous Roll, 2.0" x 250', VL, White, 250 ft/roll

<b>Article Number</b>	558-00313
<b>Type</b>	HT2WH250
<b>Color</b>	White (WH)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Continuous Vinyl Labels are made with UV-stable materials for long outdoor life.</li><li>• Labels are extruded in the actual color and not colored using surface inks for long-term fade resistance.</li><li>• Continuous Vinyl is provided in continuous rolls so that the markers can be printed and cut to any length using HellermannTyton thermal transfer printing systems.</li></ul>
<b>Quantity Per</b>	roll

**Product Description**

Continuous Vinyl Labels are made with UV-stable materials for long outdoor life. The labels are extruded in the actual color and not colored using surface inks for long-term fade resistance. Vinyl labels are provided in continuous rolls so that the markers can be printed and cut to any length using HellermannTyton thermal transfer printing systems. Good for all surface types except powder coat painted or low surface energy substrates such as polypropylene. Test on these surfaces before approving.

**Short Description**

Adhesive Labels, Solid Color Continuous Roll, 2.0" x 250', VL, White, 250 ft/roll

**Global Part Name**

HT2WH250-V-WH

**Technical Description**

Solid Colored Continuous Roll, 2.0" X 250', White

**Length L (Imperial)**

250.0

**Length L (Metric)**

76.20

**Variant**

3.2mil, 50lb bleached kraft paper

**Width W (Imperial)**

2.0

**Width W (Metric)**

50.8

**Height H (Imperial)**

2.0

**Height H (Metric)**

50.80

**Width of Liner (Metric)**

50.8

**Width of Liner (imperial)**

2.0

<b>Material</b>	Vinyl
<b>Material Shortcut</b>	V
<b>Adhesive</b>	Acrylic
<b>UV Resistant (Yes/No)</b>	Yes
<b>Adhesive Operating Temperature</b>	-40°F to +180°F (-40°C to +82°C)
<b>Operating Temperature (Metric)</b>	-40°F to +180°F (-40°C to +82°C)
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	UL 969
<b>UL Recognized (US)</b>	Yes
<b>Package Quantity(Imperial)</b>	250
<b>Package Quantity (Metric)</b>	76.20
<b>Customs Number</b>	3919102055
<b>Labels per Column</b>	1
<b>Labels per Row</b>	1

