

Specification Sheet

Part Number: TAG14J-450

Product Image Ink Jet Label, .375" x 1.0", 144 Per Sheet, 450 Material, White, 5000/pkg

| | |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number | 593-14450 |
| Type | TAG14J |
| Color | White (WH) |
| Features & Benefits | <ul style="list-style-type: none">•Ink jet printable polyester has a smooth surface, allowing for the highest resolution and print contrast.•The acrylic-based adhesive bonds to a wide variety of substrates and resists abrasion.•When used with black pigment-based inks, the material can withstand chemicals and solvents. |
| Quantity Per | pack |
| Product Description | HellermannTyton white polyester labels are ideal for marking small electrical and electronic components, such as EPROMS', Integrated circuits, as well as the circuit board itself. Printed labels can withstand the soldering process and survive flux removal when the board is washed. HellermannTyton's 450 material is designed for use on flat surfaces and can also be used to identify connectors, buttons and just about anything requiring permanent, durable, high temperature marking. |
| Short Description | Ink Jet Label, .375" x 1.0", 144 Per Sheet, 450 Material, White, 5000/pkg |
| Global Part Name | TAG14J-450-WH |
| Width W (Imperial) | 0.375 |
| Width W (Metric) | 9.52 |

| | |
|---------------------------------------|--------------------------------------------|
| Thickness T (Metric) | 64.0 |
| Height H (Imperial) | 1.0 |
| Height H (Metric) | 25.4 |
| Material | Type 450, Polyethylene Terephthalate (PET) |
| Material Shortcut | 450 |
| Adhesive | Acrylic |
| Halogen free | No |
| Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
| Operating Temperature (Metric) | -40°F to +302°F (-40°C to +150°C) |
| Reach Complaint(Article 33) | Yes |
| ROHS Complaint | Yes |
| Package Quantity(Imperial) | 2500 |
| Package Quantity (Metric) | 5000 |
| Content Unit(BMEcat) | pcs. |
| Labels per Column | 9 |

Labels per Row

16

Weight (Metric)

0.521

Weight (Imperial)

1.14