

Specification Sheet

Part Number: TAGPP1-788



Laser Tag Label, .63" x .31", 360 Per Sheet, PET, White, 1000/pkg

Article Number

594-01788

Type

TAGPP1L

Color

White (WH)

Features & Benefits

- White polyester has a smooth surface, allowing for the highest resolution and print contrast.
- The acrylic-based adhesive bonds to a wide variety of substrates and resists abrasion.
- LaserTags are sheet fed for easy loading and fast printing.

Quantity Per

pack

| | |
|---------------------------------------|--|
| Product Description | HellermannTyton white polyester labels are ideal for marking small electrical and electronic components, such as EPROMS', Integrated circuits, as well as the circuit board itself. Printed labels can withstand the soldering process and survive flux removal when the board is washed. HellermannTyton's 788 material is designed for use on flat surfaces and can also be used to identify connectors, buttons and just about anything requiring permanent, general purpose marking. |
| Short Description | Laser Tag Label, .63" x .31", 360 Per Sheet, PET, White, 1000/pkg |
| Global Part Name | TAGPP1L-788-WH |
| Width W (Imperial) | 0.625 |
| Width W (Metric) | 15.87 |
| Bundle Diameter Min (Imperial) | .22 |
| Bundle Diameter Min (Metric) | 5.80 |
| Thickness T (Metric) | 64.0 |
| Height H (Imperial) | 0.37 |
| Height H (Metric) | 9.40 |
| Material | Type 788, Polyester (788) |
| Material Shortcut | 788 |

| | |
|---------------------------------------|----------------------------------|
| Adhesive | Acrylic |
| Halogen free | No |
| Adhesive Operating Temperature | -40°F to +199°F (-40°C to +93°C) |
| Operating Temperature (Metric) | -40°F to +199°F (-40°C to +93°C) |
| Reach Complaint(Article 33) | Yes |
| ROHS Complaint | Yes |
| Package Quantity(Imperial) | 1000 |
| Package Quantity (Metric) | 1000 |
| Customs Number | 3919905060 |
| Labels per Column | 30 |
| Labels per Row | 12 |
| Weight (Metric) | 0.521 |
| Weight (Imperial) | 1.14 |

