

## Specification Sheet

Part Number: TAG52L-105

Laser printable self-laminating polyester has a smooth surface, allowing for the highest resolution and print contrast.

The material is 1.0 mil thick, allowing it to conform around wires and cable.



The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.

Lasertags are not affected by the high heat required in a laser printer.

Laser Tag Label, Self-Laminating, 2.0" x .47" x 1.33", 21 Per Sheet, PET, White, 1000/pkg

Article Number 594-52105

Type TAG52L

Color White (WH)

Quantity Per pack

Product Description HellermannTyton's self-laminating labels are used for marking wires and cable. The clear tail overlaps and protects the printed information from abrasion, chemicals and solvents and resists UV exposure. When printed using a laser printer, clear marking and high high-contrast imaging against the wire make this the perfect choice for durable identification.

|                                 |   |
|---------------------------------|---|
| Short Description               | Laser Tag Label, Self-Laminating, 2.0" x .47" x 1.33", 21 Per Sheet, PET, White, 1000/pkg |
| Global Part Name                | TAG52L-105-WH   |
| Width W (Imperial)              | 2.0   |
| Width W (Metric)                | 50.8  |
| Bundle Diameter Min (Imperial)  | 0.22  |
| Bundle Diameter Min (Metric)    | 5.80  |
| Bundle Diameter Max (Imperial)  | .45   |
| Bundle Diameter Max (Metric)    | 11.60   |
| Thickness T (Metric)            | 35.0  |
| Width of Liner (Metric)         | 215.00  |
| Width of Liner (Imperial)       | 8.5   |
| Outside Diameter Max (Imperial) | 0.299   |
| Outside Diameter Min (Metric)   | 3.8   |
| Outside Diameter Min (Imperial) | 0.15  |
| Outside Diameter Max (Metric)   | 7.60  |

|                                |                                   |
|--------------------------------|-----------------------------------|
| Material                       | Type 105, Polyester, white (105)  |
| Material Shortcut              | 105                               |
| Adhesive                       | Acrylic                           |
| Halogen Free                   | No                                |
| Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
| Operating Temperature          | -40°F to +300°F (-40°C to +149°C) |
| Reach Compliant (Article 33)   | Yes                               |
| ROHS Compliant                 | Yes                               |
| Package Quantity (Imperial)    | 1000                              |
| Package Quantity (Metric)      | 1000                              |
| Customs Number                 | 3919905060                        |
| Labels per Column              | 7                                 |
| Labels per Row                 | 3                                 |

